

AS/NZS 4268:2017

## TEST REPORT

For

### Shenzhen RAKwireless Technology Co., Ltd.

Room 506, Bldg B, New Compark, Pingshan First Road, Taoyuan Street, XiLi town  
Nanshan District, Shenzhen, China

**Model: RAK7268**

<b>Report Type:</b> Original Report	<b>Product Type:</b> WisGate
<b>Report Number:</b> RSZ200922006-14C	
<b>Report Date:</b> 2021-01-12	
Nancy Wang	
<b>Reviewed By:</b> RF Engineer	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '\*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
<b>SYSTEM TEST CONFIGURATION .....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
SPECIAL ACCESSORIES .....	7
EQUIPMENT MODIFICATIONS .....	7
SUPPORT EQUIPMENT LIST AND DETAILS .....	7
EXTERNAL I/O CABLE .....	7
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS .....</b>	<b>8</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>9</b>
<b>ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.2 – RF OUTPUT POWER .....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
LIMIT .....	10
TEST PROCEDURE .....	10
TEST DATA .....	11
<b>ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.3 - POWER SPECTRAL DENSITY .....</b>	<b>12</b>
APPLICABLE STANDARD .....	12
TEST PROCEDURE .....	12
TEST SETUP BLOCK DIAGRAM .....	15
TEST DATA .....	15
<b>ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.7 – OCCUPIED CHANNEL BANDWIDTH.....</b>	<b>16</b>
APPLICABLE STANDARD .....	16
TEST PROCEDURE .....	16
TEST DATA .....	17
<b>ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.8 – TRANSMITTER UNWANTED EMISSION IN THE OUT-OF-BAND DOMAIN.....</b>	<b>18</b>
APPLICABLE STANDARD .....	18
TEST PROCEDURE .....	18
TEST DATA .....	18
<b>ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.9 – TRANSMITTER UNWANTED EMISSION IN THE SPURIOUS DOMAIN .....</b>	<b>19</b>
APPLICABLE STANDARD .....	19
TEST PROCEDURE .....	19
TEST DATA .....	20
<b>ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.10 – RECEIVER SPURIOUS EMISSIONS.....</b>	<b>21</b>
APPLICABLE STANDARD .....	21
TEST PROCEDURE .....	21
TEST DATA .....	21

<b>ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.11 - RECEIVER BLOCKING .....</b>	<b>23</b>
APPLICABLE STANDARD .....	23
TEST PROCEDURE .....	25
TEST DATA .....	27
<b>EXHIBIT A - E.2 INFORMATION AS REQUIRED BY EN 300 328 V2.2.2, CLAUSE 5.4.1.....</b>	<b>28</b>
<b>EXHIBIT B - EUT PHOTOGRAPHS .....</b>	<b>33</b>
<b>EXHIBIT C - TEST SETUP PHOTOGRAPHS .....</b>	<b>34</b>
RADIATED SPURIOUS EMISSIONS TEST VIEW (BELOW 1GHz) .....	34
RADIATED SPURIOUS EMISSIONS TEST VIEW (ABOVE 1GHz) .....	34
<b>APPENDIX .....</b>	<b>35</b>
APPENDIX A: RF OUTPUT POWER.....	35
APPENDIX B: POWER SPECTRAL DENSITY .....	36
APPENDIX C: OCCUPIED CHANNEL BANDWIDTH .....	41
APPENDIX D: TRANSMITTER UNWANTED EMISSIONS IN THE OUT-OF-BAND DOMAIN .....	48
APPENDIX E: RECEIVER BLOCKING .....	82

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Product	WisGate
Tested Model	RAK7268
Frequency Range	2.4G Wi-Fi: 2412~2472MHz / 2422~2462MHz
Transmit Power	2.4G Wi-Fi: 9.43dBm(802.11b), 9.87dBm(802.11g) 9.93dBm(802.11n-HT20), 9.83dBm(802.11n-HT40)
Modulation Technique	WIFI: DSSS, OFDM
Antenna Specification*	1.75 dBi(It is provided by the manufacturer)
Voltage Range	DC 12.0V from adapter or DC 48V from POE
Date of Test	2020-08-25 to 2020-12-14
Sample serial number	RSZ200812004-RF-S1 (Assigned by BACL, Shenzhen)
Received date	2020-09-22
Sample/EUT Status	Good condition
Normal/Extreme Condition*	N.V.: Nominal Voltage: 230V <sub>AC</sub> L.T.: Low Temperature -10°C; N.T.: Normal Temperature +25°C; H.T.: High Temperature +55°C <i>Note: the extreme test condition was declared by manufacturer.</i>
Adapter information	Model: RA040-1202000AU Input: AC 100-240V~ 50/60Hz, 0.6A Max Output: DC 12.0V, 2.0A 24.0W

### Objective

According to section 6.1 and 7.1 of AS/NZS 4268:2017, evidence of compliance to this standard may be demonstrated by providing a complete ETSI or FCC test report. CE shall comply with the requirements of ETSI EN 300 328, so all the test items were performed in according with ETSI EN 300 328 V2.2.2 (2019-07), please refer to the CE report RSZ200812004-22B issued on 2021-01-13.

This report is in accordance with ETSI EN 300 328 V2.1.1 (2016-11), Wideband transmission systems; Data transmission equipment operating in the 2, 4 GHz ISM band and using wide band modulation techniques; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU.

The objective is to determine the compliance of EUT with ETSI EN 300 328 V2.2.2 (2019-07).

### Test Methodology

All measurements contained in this report were conducted with ETSI EN 300 328 V2.2.2 (2019-07).

**Measurement Uncertainty**

Parameter	Flab
Occupied Channel Bandwidth	$\pm 5\%$
RF output power, conducted	$\pm 0.73\text{dB}$
Unwanted Emission, conducted	$\pm 1.6\text{dB}$
Below 1GHz emissions, radiated	$\pm 4.75\text{dB}$
Above 1GHz emissions, radiated	$\pm 4.88\text{dB}$
Temperature	$\pm 1^\circ\text{C}$
Supply voltages	$\pm 0.4\%$
Time	$\pm 1\%$

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

EUT was tested with Channel 1, 7 and 13.

For 802.11n-HT40 mode, 9 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	8	2457
4	2437	9	2462
5	2442	/	/

EUT was tested with Channel 1, 5 and 9.

### EUT Exercise Software

“SecurCRT.exe”\* exercise software was used. The software and power level was provided by the manufacturer.

The worst case was performed under:

Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1 Mbps	9	9	9
802.11g	6 Mbps	3	3	3
802.11n-HT20	MCS0	3	3	3
802.11n-HT40	MCS0	3	3	3

The above data rate is the worst case for every modulation according to the EIRP test.

Note: For this product, two antennas were used, and 802.11b/g/n20/n40 all support SISO&MIMO mode, the pre-scan result for MIMO mode is the worst.

**Special Accessories**

No special accessory.

**Equipment Modifications**


No modification was made to the EUT.

**Support Equipment List and Details**

Manufacturer	Description	Model	Serial Number
/	/	/	/

**External I/O Cable**

Cable Description	Length (m)	From Port	To
Un-shielding Detachable DC Cable	1.0	EUT	Adapter

**Block Diagram of Test Setup**

**SUMMARY OF TEST RESULTS**

Rules	Description of Test	Test Result
EN 300 328 §4.3.2.2	RF output power	Compliance
EN 300 328 § 4.3.2.3	Power Spectral Density	Compliance
EN 300 328 § 4.3.2.4	Duty Cycle, Tx-sequence, Tx-gap	Not Applicable
EN 300 328 § 4.3.2.5	Medium Utilization (MU) factor	Not Applicable
EN 300 328 § 4.3.2.6	Adaptivity	Not Applicable**
EN 300 328 § 4.3.2.7	Occupied Channel Bandwidth	Compliance
EN 300 328 § 4.3.2.8	Transmitter unwanted emissions in the out-of-band domain	Compliance
EN 300 328 § 4.3.2.9	Transmitter unwanted emissions in the spurious domain	Compliance
EN 300 328 § 4.3.2.10	Receiver spurious emissions	Compliance
EN 300 328 § 4.3.2.11	Receiver Blocking	Compliance
EN 300 328 § 4.3.2.12	Geo-location capability	Not Applicable*

**Note:**

The supplier declared that the equipment is adaptive equipment

Not Applicable – This item only for non-adaptive equipment

Not Applicable\* –The supplier declared that the equipment has no this function.

Not Applicable\*\* –The test item does not apply for equipment within a maximum RF output power level of less than 10 dBm (e.i.r.p).



**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Radiated Emission Test</b>					
R&S	EMI Test Receiver	ESR3	102455	2020/08/04	2021/08/03
Sonoma instrument	Pre-amplifier	310 N	186238	2020/08/04	2021/08/03
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017/12/22	2020/12/21
COM-POWER	Dipole Antenna	AD-100	721027	NCR	NCR
Unknown	Cable 2	RF Cable 2	F-03-EM197	2019/11/29	2020/11/28
Unknown	Cable	Chamber Cable 1	F-03-EM236	2019/11/29	2020/11/28
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2020/08/04	2021/08/03
COM-POWER	Pre-amplifier	PA-122	181919	2019/11/29	2020/11/28
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017/12/22	2020/12/21
A.H.System	Horn Antenna	SAS-200/571	135	2018/09/01	2021/08/31
Insulated Wire Inc.	RF Cable	SPS-2503-3150	02222010	2019/11/29	2020/11/28
Unknown	RF Cable	W1101-EQ1 OUT	F-19-EM005	2019/11/29	2020/11/28
SNSD	Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2020/04/20	2021/04/20
Agilent	Signal Generator	N5183A	MY51040755	2020/01/14	2021/01/13
<b>RF Conducted test</b>					
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50-146520-wh	2020/08/04	2021/08/03
Tonscend Corporation	RF control Unit	JS0806-2	19D8060154	2020/08/04	2021/08/03
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40	101473	2020/08/04	2021/08/03
Agilent	MXG Vector Signal Generator	N5182B	MY53051503	2020/08/04	2021/08/03
Agilent	Signal Generator	N5183A	MY51040755	2020/01/14	2021/01/13
ESPEC	Temperature & Humidity Chamber	EL-10KA	9107726	2020/01/05	2021/01/05
Unknown	Cable 2	RF Cable 2	F-03-EM197	2020/11/29	2021/11/28

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.2 – RF OUTPUT POWER

### Applicable Standard

This requirement applies to all types of equipment using wide band modulations other than FHSS.

The RF output power is defined as the mean equivalent isotropic radiated power (e.i.r.p.) of the equipment during a transmission burst.

### Limit

The RF output power for non-FHSS equipment shall be equal to or less than 20 dBm.

NOTE: For Non-adaptive FHSS equipment, the manufacturer may have declared a reduced RF Output Power (see clause 5.4.1 m)) and associated Duty Cycle (see clause 5.4.1 e)) that will ensure that the equipment meets the requirement for the Medium Utilization (MU) factor further described in clause 4.3.2.5. This is verified by the conformance test referred to in clause 4.3.2.5.4.

For non-adaptive non-FHSS equipment, where the manufacturer has declared an RF output power of less than 20 dBm e.i.r.p., the RF output power shall be equal to or less than that declared value.

This limit shall apply for any combination of power level and intended antenna assembly.

### Test Procedure

The test procedure shall be as follows:

#### Step 1:

- Use a fast power sensor with a minimum sensitivity of -40 dBm and capable of minimum 1 MS/s.
  - Use the following settings:
    - Sample speed 1 MS/s or faster.
    - The samples shall represent the RMS power of the signal.
    - Measurement duration: For non-adaptive equipment: equal to the observation period defined in clause 4.3.1.3.2 or clause 4.3.2.4.2. For adaptive equipment, the measurement duration shall be long enough to ensure a minimum number of bursts (at least 10) is captured.
- For adaptive equipment, to increase the measurement accuracy, a higher number of bursts may be used.

#### Step 2:

- For conducted measurements on devices with one transmit chain:
  - Connect the power sensor to the transmit port, sample the transmit signal and store the raw data. Use these stored samples in all following steps.
- For conducted measurements on devices with multiple transmit chains:
  - Connect one power sensor to each transmit port for a synchronous measurement on all transmit ports.
  - Trigger the power sensors so that they start sampling at the same time. Make sure the time difference between the samples of all sensors is less than 500 ns.
  - For each individual sampling point (time domain), sum the coincident power samples of all ports and store them. Use these summed samples as the new stored data set.

#### Step 3:

- Find the start and stop times of each burst in the stored measurement samples.

The start and stop times are defined as the points where the power is at least 30 dB below the highest value of the stored samples in step 2.

In case of insufficient sensitivity of the power sensor (e.g. in case of radiated measurements), the value of 30 dB may need to be reduced appropriately.

**Step 4:**

- Between the start and stop times of each individual burst calculate the RMS power over the burst using the formula below. The start and stop points shall be included. Save these  $P_{burst}$  values, as well as the start and stop times for each burst.

$$P_{burst} = \frac{1}{k} \sum_{n=1}^k P_{sample}(n)$$

with k being the total number of samples and n the actual sample number.

**Step 5:**

- The highest of all  $P_{burst}$  values (value A in dBm) will be used for maximum e.i.r.p. calculations.

**Step 6:**

- Add the (stated) antenna assembly gain G in dBi of the individual antenna.
- In case of smart antenna systems operating in mode with beamforming (see clause 5.3.2.2.4), add the additional beamforming gain Y in dB.
- If more than one antenna assembly is intended for this power setting, the maximum overall antenna gain (G or G + Y) shall be used.
- The RF Output Power ( $P_{out}$ ) shall be calculated using the formula below:  

$$P_{out} = A + G + Y$$
- This value, which shall comply with the limit given in clause 4.3.1.2.3 or clause 4.3.2.2.3, shall be recorded in the test report.

**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Bravos Zhao on 2020-12-14.*

*EUT operation mode: Transmitting*

*Test Result: Compliant. Please refer to the Appendix.*

**ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.3 - POWER SPECTRAL DENSITY****Applicable Standard**

The Power Spectral Density is the mean equivalent isotropically radiated power (e.i.r.p.) spectral density in a 1 MHz bandwidth during a transmission burst.

The maximum Power Spectral Density for non-FHSS equipment is 10 dBm per MHz.

**Test Procedure**

Option 1: For equipment with continuous and non-continuous transmissions

The transmitter shall be connected to a spectrum analyser and the Power Spectral Density as defined in clause 4.3.2.3 shall be measured and recorded.

The test procedure shall be as follows:

**Step 1:**

Connect the UUT to the spectrum analyser and use the following settings:

- Start Frequency: 2 400 MHz
- Stop Frequency: 2 483,5 MHz
- Resolution BW: 10 kHz
- Video BW: 30 kHz
- Sweep Points: > 8 350; for spectrum analysers not supporting this number of sweep points, the frequency band may be segmented
- Detector: RMS
- Trace Mode: Max Hold
- Sweep time: For non-continuous transmissions:  $2 \times \text{Channel Occupancy Time} \times \text{number of sweep points}$

For non-adaptive equipment use the maximum TX-sequence time in the formula above instead of the Channel Occupancy Time

For continuous transmissions: 10 s; the sweep time may be increased further until a value where the sweep time has no further impact anymore on the RMS value of the signal

For non-continuous signals, wait for the trace to stabilize.

Save the data (trace data) set to a file.

**Step 2:**

For conducted measurements on smart antenna systems using either operating mode 2 or operating mode 3 (see clause 5.3.2.2), repeat the measurement for each of the transmit ports. For each sampling point (frequency domain), add up the coincident power values (in mW) for the different transmit chains and use this as the new data set.

**Step 3:**

Add up the values for power for all the samples in the file using the formula below.

$$P_{Sum} = \frac{1}{k} \sum_{n=1}^k P_{sample}(n)$$

with 'k' being the total number of samples and 'n' the actual sample number

**Step 4:**

Normalize the individual values for power (in dBm) so that the sum is equal to the RF Output Power (e.i.r.p.) measured in clause 5.4.2 and save the corrected data. The following formulas can be used:

$$C_{Corr} = P_{Sum} - P_{e.i.r.p}$$

$$P_{Samplecorr}(n) = P_{Sample}(n) - C_{Corr}$$

with 'n' being the actual sample number

**Step 5:**

Starting from the first sample  $P_{Samplecorr}(n)$  (lowest frequency), add up the power (in mW) of the following samples representing a 1 MHz segment and record the results for power and position (i.e. sample #1 to sample #100). This is the Power Spectral Density (e.i.r.p.) for the first 1 MHz segment which shall be recorded.

**Step 6:**

Shift the start point of the samples added up in step 5 by one sample and repeat the procedure in step 5 (i.e. sample #2 to sample #101).

**Step 7:**

Repeat step 6 until the end of the data set and record the Power Spectral Density values for each of the 1 MHz segments.

From all the recorded results, the highest value is the maximum Power Spectral Density for the UUT. This value, which shall comply with the limit given in clause 4.3.2.3.3, shall be recorded in the test report.

Option 2: For equipment with continuous transmission capability.

This option is for equipment that can be configured to operate in a continuous transmit mode (100 % DC) .

**Step 1:**

Connect the UUT to the spectrum analyser and use the following settings:

Centre Frequency: The centre frequency of the channel under test

RBW: 1 MHz

VBW: 3 MHz

Frequency Span:  $2 \times$  Nominal Bandwidth (e.g. 40 MHz for a 20 MHz channel)

Detector Mode: Peak

Trace Mode: Max Hold

**Step 2:**

When the trace is complete, find the peak value of the power envelope and record the frequency.

**Step 3:**

Make the following changes to the settings of the spectrum analyser:

Centre Frequency: Equal to the frequency recorded in step 2

Frequency Span: 3 MHz

RBW: 1 MHz

VBW: 3 MHz

Sweep Time: 1 minute

Detector Mode: RMS

Trace Mode: Max Hold


**Step 4:**

- Wait until the trace has stabilized, the trace shall be captured using the "Hold" or "View" option on the spectrum analyser.
- Find the peak value of the trace and place the analyser marker on this peak. This level is recorded as the highest mean power (power spectral density) D in a 1 MHz band.
- Alternatively, where a spectrum analyser is equipped with a function to measure power spectral density, this function may be used to display the power spectral density D in dBm / MHz.
- In case of conducted measurements on smart antenna systems operating in a mode with multiple transmit chains active simultaneously, the power spectral density of each transmit chain shall be measured separately to calculate the total power spectral density (value D in dBm / MHz) for the UUT.

**Step 5:**

- The maximum Power Spectral Density (PSD) e.i.r.p. is calculated from the above measured power spectral density D, the applicable antenna assembly gain G in dBi and if applicable the beamforming gain Y in dB, according to the formula below. This value shall be recorded in the test report. If more than one antenna assembly is intended for this power setting, the gain of the antenna assembly with the highest gain shall be used.

$$\text{PSD} = D + G + Y \text{ (dBm / MHz)}$$

**Test Setup Block diagram****Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Bravos Zhao on 2020-12-14.*

*EUT operation mode: Transmitting*

*Test Result: Compliant. Please refer to the Appendix.*

## **ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.7 – OCCUPIED CHANNEL BANDWIDTH**

---

### **Applicable Standard**

According to ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.7.2, the occupied channel bandwidth is the bandwidth that contains 99 % of the power of the signal.

Limit:

The Occupied Channel Bandwidth shall fall completely within the band given in table 1.

In addition, for non-adaptive non-FHSS equipment with e.i.r.p. greater than 10 dBm, the Occupied Channel Bandwidth shall be equal to or less than 20 MHz.

### **Test Procedure**

For Conducted measurement, the measurement procedure shall be as follows:

#### **Step 1:**

Connect the UUT to the spectrum analyser and use the following settings:

- Centre Frequency: The centre frequency of the channel under test
- Resolution BW: ~ 1 % of the span without going below 1 %
- Video BW:  $3 \times \text{RBW}$
- Frequency Span:  $2 \times \text{Nominal Channel Bandwidth}$
- Detector Mode: RMS
- Trace Mode: Max Hold
- Sweep time: 1 s

#### **Step 2:**

Wait for the trace to stabilize.

Find the peak value of the trace and place the analyser marker on this peak.

#### **Step 3:**

Use the 99 % bandwidth function of the spectrum analyser to measure the Occupied Channel Bandwidth of the UUT. This value shall be recorded.

NOTE: Make sure that the power envelope is sufficiently above the noise floor of the analyser to avoid the noise signals left and right from the power envelope being taken into account by this measurement.

For Radiated measurement, the test set up as described in annex B and the applicable measurement procedures described in annex C shall be used. Alternatively, a test fixture may be used.

The test procedure is as described under clause 5.4.7.2.1.



**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Bravos Zhao on 2020-12-14.*

*EUT operation mode: Transmitting*

*Test Result: Compliant. Please refer to the Appendix.*


## ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.8 – TRANSMITTER UNWANTED EMISSION IN THE OUT-OF-BAND DOMAIN

### Applicable Standard

According to ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.8.2, Transmitter unwanted emissions in the out-of-band domain are emissions when the equipment is in Transmit mode, on frequencies immediately outside the necessary bandwidth which results from the modulation process, but excluding spurious emissions.

Limit:

The transmitter unwanted emissions in the out-of-band domain shall not exceed the values provided by the mask in figure 3.



**Figure 3: Transmit mask**

### Test Procedure

The conformance tests for this requirement are defined in clause 5.4.8.

### Test Data

#### Environmental Conditions

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Bravos Zhao on 2020-12-14.*

*EUT operation mode: Transmitting*

*Test Result: Compliant. Please refer to the Appendix.*

## ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.9 – TRANSMITTER UNWANTED EMISSION IN THE SPURIOUS DOMAIN

### Applicable Standard

In the present document, transmitter unwanted emissions in the spurious domain are emissions outside the allocated band and outside the Out-of-band Domain as indicated in figure 3 when the equipment is in Transmit mode.

The transmitter unwanted emissions in the spurious domain shall not exceed the values given in table 12.

In case of equipment with antenna connectors, these limits apply to emissions at the antenna port (conducted). For emissions radiated by the cabinet or emissions radiated by integral antenna equipment (without antenna connectors), these limits are e.r.p. for emissions up to 1 GHz and as e.i.r.p. for emissions above 1 GHz.

**Transmitter limits for spurious emissions**

Frequency Range	Maximum power e.r.p ( $\leq 1$ GHz) e.i.r.p ( $> 1$ GHz)	Bandwidth
30 MHz to 47 MHz	-36 dBm	100 kHz
47 MHz to 74 MHz	-54 dBm	100 kHz
74 MHz to 87,5 MHz	-36 dBm	100 kHz
87,5 MHz to 118 MHz	-54 dBm	100 kHz
118 MHz to 174 MHz	-36 dBm	100 kHz
174 MHz to 230 MHz	-54 dBm	100 kHz
230 MHz to 470 MHz	-36 dBm	100 kHz
470 MHz to 694 MHz	-54 dBm	100 kHz
694 MHz to 1 GHz	-36 dBm	100 kHz
1 GHz to 12,75 GHz	-30 dBm	1MHz

### Test Procedure

#### Conducted measurement

In case of conducted measurements, the radio equipment shall be connected to the measuring equipment via a suitable attenuator.

The spectrum in the spurious domain (see figures 1 or 3) shall be searched for emissions that exceed the limit values given in table or that come to within 6 dB below these limits. Each occurrence shall be recorded.

The measurement procedure refer to ETSI EN 300 328 V2.2.2 (2019-07) §5.4.9.2.1

Radiated measurement:

The test site as described in annex B and applicable measurement procedures as described in Annex A shall be used.

The test procedure is further as described under clause 5.4.9.2.1.

## Test Data

### Environmental Conditions

Temperature:	29°C
Relative Humidity:	59 %
ATM Pressure:	101.0 kPa

The testing was performed by Harris He on 2020-09-14 for below 1GHz and Lovan Liang on 2020-08-25 for above 1GHz.

EUT operation mode: Transmitting (Prescan all models, worst case is RAK 7268C with Lora module RAK2287.)

Note: Pretest with 802.11b, 802.11g, 802.11n-HT20, 802.11n-HT40 the worst case was 802.11b mode.

Test Result: Compliance

**30 MHz ~ 12.75 GHz: Worst case at adapter1 (Model: PSY1202000EU)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	EN 300 328	
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd/dBi)		Limit (dBm)	Margin (dB)
802.11b - Low Channel										
479.9	36.46	222	1.6	H	-62.1	1.03	0.0	-63.13	-54	9.13
479.9	28.13	155	2.4	V	-69.5	1.03	0.0	-70.53	-54	16.53
4824.00	44.13	220	1.0	H	-57.6	1.60	12.10	-47.10	-30	17.10
4824.00	43.78	245	1.4	V	-56.8	1.60	12.10	-46.30	-30	16.30
802.11b - High Channel										
968.6	37.76	189	1.4	H	-62.8	1.37	0.0	-64.17	-36	28.17
968.6	38.84	275	1.3	V	-60.5	1.37	0.0	-61.87	-36	25.87
4944.00	45.19	31	1.2	H	-56.8	1.60	12.10	-46.30	-30	16.30
4944.00	45.12	160	2.1	V	-57.1	1.60	12.10	-46.60	-30	16.60

**Note 1:** The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

**Note 2:**

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

## ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.10 – RECEIVER SPURIOUS EMISSIONS

### Applicable Standard

According to ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.10, the receiver spurious emissions are emissions at any frequency when the equipment is in receive mode.

The spurious emissions of the receiver shall not exceed the values given in table 13.

In case of non-FHSS equipment with antenna connectors, these limits apply to emissions at the antenna port (conducted). For emissions radiated by the cabinet or for emissions radiated by integral antenna equipment (without antenna connectors), these limits are e.r.p. for emissions up to 1 GHz and e.i.r.p. for emissions above 1 GHz.

Frequency range	Maximum power, e.r.p.	Measurement bandwidth
30 MHz to 1 GHz	-57 dBm	100 kHz
1 GHz to 12,75 GHz	-47 dBm	1 MHz

### Test Procedure

Conducted measurement:

In case of conducted measurements, the radio equipment shall be connected to the measuring equipment via a suitable attenuator.

The spectrum in the spurious domain (see figures 1 or 3) shall be searched for emissions that exceed the limit values given in table or that come to within 6 dB below these limits. Each occurrence shall be recorded.

The measurement procedure refer to ETSI EN 300 328 V2.2.2 (2019-07) §5.4.10.2.1

Radiated measurement

The test site as described in annex B and applicable measurement procedures as described in Annex A shall be used.

The test procedure is further as described under clause 5.4.10.2.1.

### Test Data

#### Environmental Conditions

Temperature:	29°C
Relative Humidity:	59 %
ATM Pressure:	101.0 kPa

*The testing was performed by Harris He on 2020-09-14 for below 1GHz and Lovan Liang on 2020-08-25 for above 1GHz.*

*EUT operation mode: Receiving (Prescan all models, worst case is RAK 7268C with Lora module RAK2287.)*

Note: Pretest with 802.11b, 802.11g, 802.11n-HT20, 802.11n-HT40, the worst case was 802.11b mode.

Test Result: Compliance

**30 MHz ~ 12.75 GHz: Worst case at adapter1 (Model: PSY1202000EU)**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	EN 300 328	
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd/dBi)		Limit (dBm)	Margin (dB)
802.11b - Low Channel										
479.9	35.79	292	1.0	H	-62.7	1.03	0.0	-63.73	-57	6.73
479.9	27.65	304	2.2	V	-70.0	1.03	0.0	-71.03	-57	14.03
1258.69	41.33	189	2.2	H	-67.5	1.60	7.30	-61.80	-47	14.80
1258.69	41.70	198	1.1	V	-67.0	1.60	7.30	-61.30	-47	14.30
802.11b - High Channel										
966.7	36.22	16	1.8	H	-64.4	1.37	0.0	-65.77	-57	8.77
966.7	37.16	277	2.1	V	-62.2	1.37	0.0	-63.57	-57	6.57
1274.52	42.41	242	1.7	H	-66.4	1.60	7.30	-60.70	-47	13.70
1274.52	41.75	150	1.1	V	-67.0	1.60	7.30	-61.30	-47	14.30

**Note 1:** The unit of antenna gain is dBd for frequency below 1GHz and is dBi for frequency above 1GHz.

**Note 2:**

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

## ETSI EN 300 328 V2.2.2 (2019-07) §4.3.2.11 - RECEIVER BLOCKING

### Applicable Standard

This requirement applies to all receiver categories as defined in clause 4.2.3.

Receiver blocking is a measure of the ability of the equipment to receive a wanted signal on its operating channel without exceeding a given degradation due to the presence of an unwanted input signal (blocking signal) at frequencies other than those of the operating band and spurious responses.

### Performance Criteria:

For equipment that supports a PER or FER test to be performed, the minimum performance criterion shall be a PER or FER less than or equal to 10 %.

For equipment that does not support a PER or a FER test to be performed, the minimum performance criterion shall be no loss of the wireless transmission function needed for the intended use of the equipment.

### Limit:

While maintaining the minimum performance criteria as defined in clause 4.3.2.11.3, the blocking levels at specified frequency offsets shall be equal to or greater than the limits defined for the applicable receiver category provided in table 14, table 15 or table 16.

**Table 14: Receiver Blocking parameters for Receiver Category 1 equipment**

Wanted signal mean power from companion device (dBm) (see notes 1 and 4)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 4)	Type of blocking signal
$(-133 \text{ dBm} + 10 \times \log_{10}(\text{OCBW}))$ or $-68 \text{ dBm}$ whichever is less (see note 2)	2 380 2 504	-34	CW
$(-139 \text{ dBm} + 10 \times \log_{10}(\text{OCBW}))$ or $-74 \text{ dBm}$ whichever is less (see note 3)	2 300 2 330 2 360 2 524 2 584 2 674		
NOTE 1: OCBW is in Hz.			
NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to $P_{\min} + 26 \text{ dB}$ where $P_{\min}$ is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.			
NOTE 3: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to $P_{\min} + 20 \text{ dB}$ where $P_{\min}$ is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.			
NOTE 4: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned as recorded in clause 5.4.3.2.2.			

**Table 15: Receiver Blocking parameters receiver Category 2 equipment**

Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 3)	Type of blocking signal
$(-139 \text{ dBm} + 10 \times \log_{10}(\text{OCBW}) + 10 \text{ dB})$ or $(-74 \text{ dBm} + 10 \text{ dB})$ whichever is less (see note 2)	2 380 2 504 2 300 2 584	-34	CW
<p>NOTE 1: OCBW is in Hz.</p> <p>NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to <math>P_{\min} + 26 \text{ dB}</math> where <math>P_{\min}</math> is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.</p> <p>NOTE 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned as recorded in clause 5.4.3.2.2.</p>			

**Table 16: Receiver Blocking parameters receiver Category 3 equipment**

Wanted signal mean power from companion device (dBm) (see notes 1 and 3)	Blocking signal frequency (MHz)	Blocking signal power (dBm) (see note 3)	Type of blocking signal
$(-139 \text{ dBm} + 10 \times \log_{10}(\text{OCBW}) + 20 \text{ dB})$ or $(-74 \text{ dBm} + 20 \text{ dB})$ whichever is less (see note 2)	2 380 2 504 2 300 2 584	-34	CW
<p>NOTE 1: OCBW is in Hz.</p> <p>NOTE 2: In case of radiated measurements using a companion device and the level of the wanted signal from the companion device cannot be determined, a relative test may be performed using a wanted signal up to <math>P_{\min} + 30 \text{ dB}</math> where <math>P_{\min}</math> is the minimum level of wanted signal required to meet the minimum performance criteria as defined in clause 4.3.1.12.3 in the absence of any blocking signal.</p> <p>NOTE 3: The level specified is the level at the UUT receiver input assuming a 0 dBi antenna assembly gain. In case of conducted measurements, this level has to be corrected for the (in-band) antenna assembly gain (G). In case of radiated measurements, this level is equivalent to a power flux density (PFD) in front of the UUT antenna with the UUT being configured/positioned as recorded in clause 5.4.3.2.2.</p>			




## Test Procedure

Conducted measurement:

For systems using multiple receive chains only one chain (antenna port) need to be tested. All other receiver inputs shall be terminated.

Figure 6 shows the test set-up which can be used for performing the receiver blocking test.



**Figure 6: Test Set-up for receiver blocking**

The procedure in step 1 to step 6 below shall be used to verify the receiver blocking requirement as described in clause 4.3.1.12 or clause 4.3.2.11. The performance monitoring device is capable of verifying the performance criteria as defined in clause 4.3.1.12.3 or clause 4.3.2.11.3.

Table 6, table 7 and table 8 in clause 4.3.1.12.4 contain the applicable blocking frequencies and blocking levels for each of the receiver categories for testing Receiver Blocking on FHSS equipment.

Table 14, table 15 and table 16 in clause 4.3.2.11.4 contain the applicable blocking frequencies and blocking levels for each of the receiver categories for testing Receiver Blocking on non-FHSS equipment.

### Step 1:

- For non-FHSS equipment, the UUT shall be set to the lowest operating channel on which the blocking test has to be performed (see clause 5.4.11.1).

### Step 2:

- The blocking signal generator is set to the first frequency as defined in the appropriate table corresponding to the receiver category and type of equipment.

### Step 3:

- With the blocking signal generator switched off, a communication link is established between the UUT and the associated companion device using the test setup shown in figure 6.

- Unless the option provided in note 2 of the applicable table referred to in clause 5.4.11.2.1 is used, the level of the wanted signal shall be set to the value provided in the table corresponding to the receiver category and type of equipment. The test procedure defined in clause 5.4.2, and more in particular clause 5.4.2.2.1.2, can be used to measure the (conducted) level of the wanted signal however no correction shall be made for antenna gain of the companion device (step 6 in clause 5.4.2.2.1.2 shall be ignored). This level may be measured directly at the output of the companion device and a correction is made for the coupling loss into the UUT. The actual level for the wanted signal shall be recorded in the test report.

- When the option provided in note 2 of the applicable table referred to in clause 5.4.11.2.1 is used, the attenuation of the variable attenuator shall be increased in 1 dB steps to a value at which the minimum performance criteria as specified in clause 4.3.1.12.3 or clause 4.3.2.11.3 is still met. The resulting level for the wanted signal at the input of the UUT is  $P_{min}$ . This signal level ( $P_{min}$ ) is increased by the value provided in note 2 of the applicable table corresponding to the receiver category and type of equipment.

**Step 4:**

- The blocking signal at the UUT is set to the level provided in the table corresponding to the receiver category and type of equipment.
- If the performance criteria as specified in clause 4.3.1.12.3 or clause 4.3.2.11.3 are met then proceed to step 6.

**Step 5:**

- If the performance criteria as specified in clause 4.3.1.12.3 or clause 4.3.2.11.3 is not met, step 3 and step 4 shall be repeated after that the frequency of the blocking signal set in step 2 has been increased with a value equal to the Occupied Channel Bandwidth except:
  - For the blocking frequency 2 380 MHz, where this frequency offset shall be less than or equal to 10 MHz. If this frequency offset is more than 7 MHz, the level of the wanted signal shall be increased by 3 dB.
  - For the blocking frequency 2 503,5 MHz, where this frequency offset shall be less than or equal to 10 MHz. If this frequency offset is more than 7 MHz, the level of the wanted signal shall be decreased by 3 dB.
- If the performance criteria as specified in clause 4.3.1.12.3 or clause 4.3.2.11.3 is still not met, step 3 and step 4 shall be repeated after that the frequency of the blocking signal set in step 2 has been decreased with a value equal to the Occupied Channel Bandwidth except:
  - For the blocking frequency 2 380 MHz, where this frequency offset shall be less than or equal to 10 MHz. If this frequency offset is more than 7 MHz, the level of the wanted signal shall be decreased by 3 dB.
  - For the blocking frequency 2 503,5 MHz, where this frequency offset shall be less than or equal to 10 MHz. If this frequency offset is more than 7 MHz, the level of the wanted signal shall be increased by 3 dB.
- If the performance criteria as specified in clause 4.3.1.12.3 or clause 4.3.2.11.3 is still not met, the UUT fails to comply with the Receiver Blocking requirement and step 6 and step 7 are no longer required.
- It shall be recorded in the test report whether the shift of blocking frequencies as described in the present step was used.

**Step 6:**

- Repeat step 4 and step 5 for each remaining combination of frequency and level for the blocking signal as provided in the table corresponding to the receiver category and type of equipment.

**Step 7:**

- For non-FHSS equipment, repeat step 2 to step 6 with the UUT operating at the highest operating channel on which the blocking test has to be performed (see clause 5.4.11.1).

**Step 8:**

- It shall be assessed and recorded in the test report whether the UUT complies with the Receiver Blocking requirement.

**Test Data****Environmental Conditions**

<b>Temperature:</b>	25 °C
<b>Relative Humidity:</b>	56 %
<b>ATM Pressure:</b>	101.0 kPa

*The testing was performed by Bravos Zhao on 2020-12-14.*

*EUT operation mode: Receiving (Worst case)*

*Test Result: Compliant. Please refer to the Appendix.*

**EXHIBIT A - E.2 INFORMATION AS REQUIRED BY EN 300 328 V2.2.2,  
CLAUSE 5.4.1**

In accordance with EN 300 328, clause 5.4.1, the following information is provided by the supplier.

**a) The type of modulation used by the equipment:**

- ☐ FHSS  
☒ other forms of modulation

**b) In case of FHSS modulation:**

In case of non-Adaptive Frequency Hopping equipment:

The number of Hopping Frequencies: \_\_\_\_\_.

In case of Adaptive Frequency Hopping Equipment:

The maximum number of Hopping Frequencies: \_\_\_\_\_;

The minimum number of Hopping Frequencies: \_\_\_\_\_;

The (average) Dwell Time: \_\_\_\_\_;

**c) Adaptive / non-adaptive equipment:**

- ☐ non-adaptive Equipment  
☒ adaptive Equipment without the possibility to switch to a non-adaptive mode  
☐ adaptive Equipment which can also operate in a non-adaptive mode

**d) In case of adaptive equipment:**

The Channel Occupancy Time implemented by the equipment: \_\_\_\_\_ms

- ☒ The equipment has implemented an LBT based DAA mechanism

In case of equipment using modulation different from FHSS:

- ☐ The equipment is Frame Based equipment  
☒ The equipment is Load Based equipment  
☐ The equipment can switch dynamically between Frame Based and Load Based equipment

The CCA time implemented by the equipment: \_\_\_\_\_µs

- ☐ The equipment has implemented an non-LBT based DAA mechanism  
☐ The equipment can operate in more than one adaptive mode

**e) In case of non-adaptive Equipment:**

The maximum RF Output Power (e.i.r.p.): \_\_\_\_\_dBm

The maximum (corresponding) Duty Cycle: \_\_\_\_\_%

Equipment with dynamic behaviour, that behaviour is described here. (e.g. the different combinations of duty cycle and corresponding power levels to be declared):

**f) The worst case operational mode for each of the following tests:**

RF Output Power: 9.93dBm;  
Power Spectral Density 1.75dBm/MHz;  
Duty cycle, Tx-Sequence, Tx-gap N/A;  
Accumulated Transmit Time, Minimum Frequency Occupation & Hopping Sequence (only for FHSS equipment)  
N/A;  
Hopping Frequency Separation (only for FHSS equipment) N/A;  
Medium Utilisation N/A;  
Adaptivity N/A;  
Receiver Blocking Pass;  
Occupied Channel Bandwidth 20MHz/40MHz;  
Transmitter unwanted emissions in the OOB domain -27.28dBm;  
Transmitter unwanted emissions in the spurious domain -63.13dBm;  
Receiver spurious emissions -63.73dBm;

**g) The different transmit operating modes (tick all that apply):**

- ☐ Operating mode 1: Single Antenna Equipment  
☐ Equipment with only 1 antenna  
☐ Equipment with 2 diversity antennas but only 1 antenna active at any moment in time  
☐ Smart Antenna Systems with 2 or more antennas, but operating in a (legacy) mode where only 1 antenna is used. (e.g. IEEE 802.11™ [i.3] legacy mode in smart antenna systems)
- ☒ Operating mode 2: Smart Antenna Systems - Multiple Antennas without beam forming  
☒ Single spatial stream / Standard throughput / (e.g. IEEE 802.11™ [i.3] legacy mode)  
☐ High Throughput (> 1 spatial stream) using Occupied Channel Bandwidth 1  
☐ High Throughput (> 1 spatial stream) using Occupied Channel Bandwidth 2  
Note: Add more lines if more channel bandwidths are supported.
- ☐ Operating mode 3: Smart Antenna Systems - Multiple Antennas with beam forming  
☐ Single spatial stream / Standard throughput (e.g. IEEE 802.11™ [i.3] legacy mode)  
☐ High Throughput (> 1 spatial stream) using Occupied Channel Bandwidth 1  
☐ High Throughput (> 1 spatial stream) using Occupied Channel Bandwidth 2  
Note: Add more lines if more channel bandwidths are supported.

**h) In case of Smart Antenna Systems:**

The number of Receive chains: 2;  
The number of Transmit chains: 2;

- ☒ symmetrical power distribution  
☐ asymmetrical power distribution

In case of beam forming, the maximum beam forming gain: N/A dB;

Note: Beam forming gain does not include the basic gain of a single antenna.

**i) Operating Frequency Range(s) of the equipment:**

Operating Frequency Range 1: 2412 MHz to 2472 MHz  
Operating Frequency Range 2: 2422 MHz to 2462 MHz

Note: Add more lines if more Frequency Ranges are supported.

**j) Nominal Channel Bandwidth(s):**Occupied Channel Bandwidth 1: 20 MHzOccupied Channel Bandwidth 2: 40 MHzOccupied Channel Bandwidth 3:      MHzOccupied Channel Bandwidth 4:      MHz

Note: Add more lines if more channel bandwidths are supported.

**k) Type of Equipment (stand-alone, combined, plug-in radio device, etc.):**

- ☒ Stand-alone  
☐ Combined Equipment (Equipment where the radio part is fully integrated within another type of equipment)  
☐ Plug-in radio device (Equipment intended for a variety of host systems)  
☐ Other                                     ;

**l) The normal and the extreme operating conditions that apply to the equipment:****Normal operating conditions (if applicable):**Operating temperature range: +25 °COther (please specify if applicable):                     **Extreme operating conditions:**Operating temperature range: Minimum: -10 °C Maximum +55 °COther (please specify if applicable):                      Minimum:                      Maximum                     

Details provided are for the: ☒ stand-alone equipment  
☐ combined (or host) equipment  
☐ test jig

**m) The intended combination(s) of the radio equipment power settings and one or more antenna assemblies and their corresponding e.i.r.p levels:**

Antenna Type:

- ☒ Integral Antenna (information to be provided in case of conducted measurements)

Antenna Gain: 1.75 dBiIf applicable, additional beamforming gain (excluding basic antenna gain):                      dB

- ☐ Temporary RF connector provided  
☐ No temporary RF connector provided
- ☐ Dedicated Antennas (equipment with antenna connector)  
☐ Single power level with corresponding antenna(s)  
☐ Multiple power settings and corresponding antenna(s)

Number of different Power Levels:                     ;Power Level 1:              dBmPower Level 2:              dBmPower Level 3:              dBm

Note 1: Add more lines in case the equipment has more power levels.

Note 2: These power levels are conducted power levels (at antenna connector).

For each of the Power Levels, provide the intended antenna assemblies, their corresponding gains (G) and the resulting e.i.r.p. levels also taking into account the beamforming gain (Y) if applicable

Power Level 1: \_\_\_\_\_ dBm

Number of antenna assemblies provided for this power level:

Assembly #	Gain (dBi)	e.i.r.p. (dBm)	Part number or model name
1			
2			
3			
4			

Note 3: Add more rows in case more antenna assemblies are supported for this power level.

Power Level 2: \_\_\_\_\_ dBm

Number of antenna assemblies provided for this power level:

Assembly #	Gain (dBi)	e.i.r.p. (dBm)	Part number or model name
1			
2			
3			
4			

Note 4: Add more rows in case more antenna assemblies are supported for this power level.

Power Level 2: \_\_\_\_\_ dBm

Number of antenna assemblies provided for this power level:

Assembly #	Gain (dBi)	e.i.r.p. (dBm)	Part number or model name
1			
2			
3			
4			

Note 5: Add more rows in case more antenna assemblies are supported for this power level.

**n) The nominal voltages of the stand-alone radio equipment or the nominal voltages of the combined (host) equipment or test jig in case of plug-in devices:**

Details provided are for the: ☒ stand-alone equipment  
☐ combined (or host) equipment  
☐ test jig

Supply Voltage ☒ AC mains State AC voltage 100-240 V  
☒ DC State DC voltage 12 or 48 V

In case of DC, indicate the type of power source

- ☐ Internal Power Supply  
☒ External Power Supply or AC/DC adapter  
☐ Battery  
☒ Other: POE Supply

**o) Describe the test modes available which can facilitate testing:**

The measurements shall be performed during continuously transmitting

**p) The equipment type (e.g. Bluetooth®, IEEE 802.11™ [i.3], proprietary, etc.):**

IEEE 802.11™ [i.3]

**q) If applicable, the statistical analysis referred to in clause 5.4.1 q)**

(to be provided as separate attachment)

**r) If applicable, the statistical analysis referred to in clause 5.4.1 r)**

(to be provided as separate attachment)

**s) Geo-location capability supported by the equipment:**

☐ Yes

☐ The geographical location determined by the equipment as defined in clause 4.3.1.13.2 or clause 4.3.2.12.2 is not accessible to the user.

☒ No



## **EXHIBIT B - EUT PHOTOGRAPHS**

---

Please refer to the Attachment.

FINAL

## **EXHIBIT C - TEST SETUP PHOTOGRAPHS**

**Radiated Spurious Emissions Test View (Below 1GHz)**



**Radiated Spurious Emissions Test View (Above 1GHz)**



## APPENDIX

### Appendix A: RF Output Power Test Result

Test Condition	Test Mode	Antenna	Channel	EIRP[dBm]	Limit[dBm]	Verdict
NTNV	11B-CDD	total	2412	9.23	20	PASS
		total	2442	8.93	20	PASS
		total	2472	9.42	20	PASS
	11G-CDD	total	2412	9.26	20	PASS
		total	2442	9.86	20	PASS
		total	2472	9.24	20	PASS
	11N20MIMO	total	2412	9.93	20	PASS
		total	2442	8.86	20	PASS
		total	2472	9.17	20	PASS
	11N40MIMO	total	2422	9.34	20	PASS
		total	2442	9.83	20	PASS
		total	2462	9.18	20	PASS
LTNV	11B-CDD	total	2412	9.36	20	PASS
		total	2442	9.04	20	PASS
		total	2472	9.43	20	PASS
	11G-CDD	total	2412	9.26	20	PASS
		total	2442	9.87	20	PASS
		total	2472	9.27	20	PASS
	11N20MIMO	total	2412	9.00	20	PASS
		total	2442	9.00	20	PASS
		total	2472	9.32	20	PASS
	11N40MIMO	total	2422	9.48	20	PASS
		total	2442	9.02	20	PASS
		total	2462	9.23	20	PASS
HTNV	11B-CDD	total	2412	9.20	20	PASS
		total	2442	8.88	20	PASS
		total	2472	9.42	20	PASS
	11G-CDD	total	2412	9.26	20	PASS
		total	2442	9.85	20	PASS
		total	2472	9.23	20	PASS
	11N20MIMO	total	2412	9.91	20	PASS
		total	2442	8.82	20	PASS
		total	2472	9.12	20	PASS
	11N40MIMO	total	2422	9.28	20	PASS
		total	2442	9.81	20	PASS
		total	2462	9.14	20	PASS


Note: Antenna gain has added into final result.


**Appendix B: Power Spectral Density  
Test Result**


Test Mode	Antenna	Channel	PSD[dBm/MHz]	Limit[dBm/MHz]	Verdict
11B-CDD	total	2412	1.75	10	PASS
	total	2442	0.51	10	PASS
	total	2472	1.00	10	PASS
11G-CDD	total	2412	-1.03	10	PASS
	total	2442	-0.21	10	PASS
	total	2472	-0.19	10	PASS
11N20MIMO	total	2412	-0.57	10	PASS
	total	2442	-1.52	10	PASS
	total	2472	-1.35	10	PASS
11N40MIMO	total	2422	-1.96	10	PASS
	total	2442	-1.32	10	PASS
	total	2462	-2.13	10	PASS


Note: Antenna gain has added into final result.

## Test Graphs













### Appendix C: Occupied Channel Bandwidth Test Result


Test Mode	Antenna	Channel	OCB[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B-CDD	Ant1	2412	14.266	2404.8070	2419.0730	2400 to 2483.5	PASS
	Ant2	2412	14.146	2404.8870	2419.0330	2400 to 2483.5	PASS
	Ant1	2472	14.226	2464.8470	2479.0730	2400 to 2483.5	PASS
	Ant2	2472	14.186	2464.8870	2479.0730	2400 to 2483.5	PASS
11G-CDD	Ant1	2412	16.424	2403.7680	2420.1920	2400 to 2483.5	PASS
	Ant2	2412	16.424	2403.7680	2420.1920	2400 to 2483.5	PASS
	Ant1	2472	16.464	2463.7680	2480.2320	2400 to 2483.5	PASS
	Ant2	2472	16.424	2463.7680	2480.1920	2400 to 2483.5	PASS
11N20MIMO	Ant1	2412	17.622	2403.1690	2420.7910	2400 to 2483.5	PASS
	Ant2	2412	17.622	2403.1690	2420.7910	2400 to 2483.5	PASS
	Ant1	2472	17.622	2463.1690	2480.7910	2400 to 2483.5	PASS
	Ant2	2472	17.622	2463.1690	2480.7910	2400 to 2483.5	PASS
11N40MIMO	Ant1	2422	36.044	2403.9380	2439.9820	2400 to 2483.5	PASS
	Ant2	2422	36.044	2403.9380	2439.9820	2400 to 2483.5	PASS
	Ant1	2462	36.044	2443.8580	2479.9020	2400 to 2483.5	PASS
	Ant2	2462	36.044	2443.9380	2479.9820	2400 to 2483.5	PASS

## Test Graphs






## 11G-CDD\_Ant1\_2472





## 11G-CDD\_Ant2\_2472




## 11N20MIMO\_Ant1\_2412









### Appendix D: Transmitter Unwanted Emissions In The Out-Of-BandDomain Test Result

Test Mode	Antenna	Channel	Freq. [MHz]	Level[dBm]	Limit[dBm]	Verdict
11BMIMO	Ant1	2412	2371.808	-41.74	-23.01	PASS
			2372.154	-42.94	-23.01	PASS
			2373.154	-43.42	-23.01	PASS
			2374.154	-43.24	-23.01	PASS
			2375.154	-43.46	-23.01	PASS
			2376.154	-43.89	-23.01	PASS
			2377.154	-43.49	-23.01	PASS
			2378.154	-43.02	-23.01	PASS
			2379.154	-42.89	-23.01	PASS
			2380.154	-43.48	-23.01	PASS
			2381.154	-43.49	-23.01	PASS
			2382.154	-42.77	-23.01	PASS
			2383.154	-42.38	-23.01	PASS
			2384.154	-42.44	-23.01	PASS
			2385.154	-43.16	-23.01	PASS
			2386.154	-42.84	-13.01	PASS
			2386.5	-42.98	-13.01	PASS
			2387.5	-43.45	-13.01	PASS
			2388.5	-42.63	-13.01	PASS
			2389.5	-43.00	-13.01	PASS
			2390.5	-44.07	-13.01	PASS
			2391.5	-42.67	-13.01	PASS
			2392.5	-41.11	-13.01	PASS
			2393.5	-38.58	-13.01	PASS
			2394.5	-37.00	-13.01	PASS
			2395.5	-36.22	-13.01	PASS
			2396.5	-31.57	-13.01	PASS
			2397.5	-31.85	-13.01	PASS
			2398.5	-30.86	-13.01	PASS
			2399.5	-32.73	-13.01	PASS
			2484	-42.25	-13.01	PASS
			2485	-43.74	-13.01	PASS
			2486	-43.98	-13.01	PASS
			2487	-44.04	-13.01	PASS
			2488	-44.25	-13.01	PASS
			2489	-43.34	-13.01	PASS
			2490	-44.12	-13.01	PASS
			2491	-43.50	-13.01	PASS
			2492	-43.79	-13.01	PASS
			2493	-44.30	-13.01	PASS
			2494	-43.55	-13.01	PASS
			2495	-43.26	-13.01	PASS
			2496	-43.51	-13.01	PASS
			2497	-44.24	-13.01	PASS
			2497.346	-43.49	-13.01	PASS
			2498.346	-44.10	-23.01	PASS
			2499.346	-43.70	-23.01	PASS
			2500.346	-42.74	-23.01	PASS
			2501.346	-43.50	-23.01	PASS
			2502.346	-43.69	-23.01	PASS
			2503.346	-43.54	-23.01	PASS
			2504.346	-43.80	-23.01	PASS
			2505.346	-43.65	-23.01	PASS
			2506.346	-42.28	-23.01	PASS
			2507.346	-43.92	-23.01	PASS



			2508.346	-44.03	-23.01	PASS
			2509.346	-43.53	-23.01	PASS
			2510.346	-43.58	-23.01	PASS
			2511.346	-43.13	-23.01	PASS
			2511.692	-43.79	-23.01	PASS
			2372.128	-42.74	-23.01	PASS
			2372.314	-43.28	-23.01	PASS
			2373.314	-43.71	-23.01	PASS
			2374.314	-42.54	-23.01	PASS
			2375.314	-42.75	-23.01	PASS
			2376.314	-42.69	-23.01	PASS
			2377.314	-43.84	-23.01	PASS
			2378.314	-43.55	-23.01	PASS
			2379.314	-41.28	-23.01	PASS
			2380.314	-42.25	-23.01	PASS
			2381.314	-41.99	-23.01	PASS
			2382.314	-43.11	-23.01	PASS
			2383.314	-42.91	-23.01	PASS
			2384.314	-42.79	-23.01	PASS
			2385.314	-42.70	-23.01	PASS
			2386.314	-41.92	-13.01	PASS
			2386.5	-42.24	-13.01	PASS
			2387.5	-41.28	-13.01	PASS
			2388.5	-42.93	-13.01	PASS
			2389.5	-42.99	-13.01	PASS
			2390.5	-40.82	-13.01	PASS
			2391.5	-40.59	-13.01	PASS
			2392.5	-41.08	-13.01	PASS
			2393.5	-42.16	-13.01	PASS
			2394.5	-41.15	-13.01	PASS
			2395.5	-41.75	-13.01	PASS
			2396.5	-39.56	-13.01	PASS
			2397.5	-40.40	-13.01	PASS
			2398.5	-38.54	-13.01	PASS
			2399.5	-39.62	-13.01	PASS
			2484	-42.99	-13.01	PASS
			2485	-42.76	-13.01	PASS
			2486	-44.19	-13.01	PASS
			2487	-43.76	-13.01	PASS
			2488	-43.46	-13.01	PASS
			2489	-43.19	-13.01	PASS
			2490	-42.80	-13.01	PASS
			2491	-43.90	-13.01	PASS
			2492	-43.95	-13.01	PASS
			2493	-43.65	-13.01	PASS
			2494	-42.54	-13.01	PASS
			2495	-43.86	-13.01	PASS
			2496	-43.02	-13.01	PASS
			2497	-43.57	-13.01	PASS
			2497.186	-43.01	-13.01	PASS
			2498.186	-43.69	-23.01	PASS
			2499.186	-43.96	-23.01	PASS
			2500.186	-43.14	-23.01	PASS
			2501.186	-43.61	-23.01	PASS
			2502.186	-43.64	-23.01	PASS
			2503.186	-43.62	-23.01	PASS
			2504.186	-43.49	-23.01	PASS
			2505.186	-42.60	-23.01	PASS
			2506.186	-43.64	-23.01	PASS
			2507.186	-43.93	-23.01	PASS
			2508.186	-43.41	-23.01	PASS

			2509.186	-43.79	-23.01	PASS
			2510.186	-43.30	-23.01	PASS
			2511.186	-42.68	-23.01	PASS
			2511.372	-43.58	-23.01	PASS
2472			2372.128	-42.88	-23.01	PASS
			2372.314	-44.05	-23.01	PASS
			2373.314	-43.85	-23.01	PASS
			2374.314	-43.05	-23.01	PASS
			2375.314	-43.27	-23.01	PASS
			2376.314	-43.51	-23.01	PASS
			2377.314	-43.25	-23.01	PASS
			2378.314	-43.31	-23.01	PASS
			2379.314	-43.53	-23.01	PASS
			2380.314	-43.55	-23.01	PASS
			2381.314	-44.19	-23.01	PASS
			2382.314	-43.42	-23.01	PASS
			2383.314	-43.57	-23.01	PASS
			2384.314	-42.77	-23.01	PASS
			2385.314	-43.63	-23.01	PASS
			2386.314	-43.43	-13.01	PASS
			2386.5	-42.88	-13.01	PASS
			2387.5	-42.55	-13.01	PASS
			2388.5	-42.20	-13.01	PASS
			2389.5	-44.02	-13.01	PASS
			2390.5	-43.46	-13.01	PASS
			2391.5	-42.98	-13.01	PASS
			2392.5	-43.19	-13.01	PASS
			2393.5	-42.97	-13.01	PASS
			2394.5	-43.30	-13.01	PASS
			2395.5	-43.48	-13.01	PASS
			2396.5	-43.98	-13.01	PASS
			2397.5	-43.50	-13.01	PASS
			2398.5	-43.52	-13.01	PASS
			2399.5	-41.72	-13.01	PASS
			2484	-39.68	-13.01	PASS
			2485	-39.84	-13.01	PASS
			2486	-39.28	-13.01	PASS
			2487	-39.94	-13.01	PASS
			2488	-40.00	-13.01	PASS
			2489	-40.69	-13.01	PASS
			2490	-41.06	-13.01	PASS
			2491	-40.98	-13.01	PASS
			2492	-41.88	-13.01	PASS
			2493	-41.71	-13.01	PASS
			2494	-43.49	-13.01	PASS
			2495	-42.97	-13.01	PASS
			2496	-43.49	-13.01	PASS
			2497	-42.36	-13.01	PASS
			2497.186	-41.88	-13.01	PASS
			2498.186	-42.66	-23.01	PASS
			2499.186	-42.43	-23.01	PASS
			2500.186	-43.79	-23.01	PASS
			2501.186	-43.19	-23.01	PASS
			2502.186	-43.29	-23.01	PASS
			2503.186	-43.15	-23.01	PASS
			2504.186	-42.42	-23.01	PASS
			2505.186	-43.26	-23.01	PASS
			2506.186	-42.91	-23.01	PASS
			2507.186	-43.39	-23.01	PASS
			2508.186	-43.01	-23.01	PASS
			2509.186	-42.11	-23.01	PASS

	Ant2	2472	2510.186	-43.32	-23.01	PASS
			2511.186	-43.23	-23.01	PASS
			2511.372	-42.96	-23.01	PASS
			2372.128	-43.06	-23.01	PASS
			2372.314	-42.97	-23.01	PASS
			2373.314	-42.71	-23.01	PASS
			2374.314	-42.73	-23.01	PASS
			2375.314	-42.33	-23.01	PASS
			2376.314	-42.41	-23.01	PASS
			2377.314	-42.43	-23.01	PASS
			2378.314	-42.96	-23.01	PASS
			2379.314	-42.41	-23.01	PASS
			2380.314	-43.34	-23.01	PASS
			2381.314	-42.83	-23.01	PASS
			2382.314	-42.93	-23.01	PASS
			2383.314	-41.88	-23.01	PASS
			2384.314	-42.62	-23.01	PASS
			2385.314	-42.96	-23.01	PASS
			2386.314	-42.71	-13.01	PASS
			2386.5	-42.87	-13.01	PASS
			2387.5	-43.22	-13.01	PASS
			2388.5	-43.03	-13.01	PASS
			2389.5	-42.55	-13.01	PASS
			2390.5	-42.98	-13.01	PASS
			2391.5	-42.36	-13.01	PASS
			2392.5	-41.77	-13.01	PASS
			2393.5	-42.66	-13.01	PASS
			2394.5	-42.14	-13.01	PASS
			2395.5	-42.09	-13.01	PASS
			2396.5	-41.91	-13.01	PASS
			2397.5	-42.88	-13.01	PASS
			2398.5	-41.51	-13.01	PASS
			2399.5	-42.03	-13.01	PASS
			2484	-42.14	-13.01	PASS
			2485	-41.88	-13.01	PASS
			2486	-42.14	-13.01	PASS
			2487	-42.43	-13.01	PASS
			2488	-42.84	-13.01	PASS
			2489	-42.84	-13.01	PASS
			2490	-42.22	-13.01	PASS
			2491	-42.70	-13.01	PASS
			2492	-42.36	-13.01	PASS
			2493	-41.83	-13.01	PASS
			2494	-42.04	-13.01	PASS
			2495	-42.05	-13.01	PASS
			2496	-42.32	-13.01	PASS
			2497	-41.57	-13.01	PASS
			2497.186	-43.03	-13.01	PASS
			2498.186	-41.61	-23.01	PASS
			2499.186	-41.94	-23.01	PASS
			2500.186	-42.02	-23.01	PASS
			2501.186	-42.18	-23.01	PASS
			2502.186	-42.67	-23.01	PASS
			2503.186	-42.05	-23.01	PASS
			2504.186	-42.29	-23.01	PASS
			2505.186	-42.70	-23.01	PASS
			2506.186	-42.57	-23.01	PASS
			2507.186	-42.11	-23.01	PASS
			2508.186	-42.39	-23.01	PASS
			2509.186	-42.72	-23.01	PASS
			2510.186	-41.83	-23.01	PASS

			2511.186	-42.24	-23.01	PASS
			2511.372	-41.58	-23.01	PASS
			2367.652	-42.13	-23.01	PASS
			2368.076	-41.96	-23.01	PASS
			2369.076	-41.76	-23.01	PASS
			2370.076	-41.89	-23.01	PASS
			2371.076	-42.08	-23.01	PASS
			2372.076	-41.22	-23.01	PASS
			2373.076	-42.13	-23.01	PASS
			2374.076	-42.57	-23.01	PASS
			2375.076	-41.36	-23.01	PASS
			2376.076	-42.16	-23.01	PASS
			2377.076	-42.19	-23.01	PASS
			2378.076	-40.88	-23.01	PASS
			2379.076	-41.90	-23.01	PASS
			2380.076	-41.85	-23.01	PASS
			2381.076	-42.47	-23.01	PASS
			2382.076	-41.60	-23.01	PASS
			2383.076	-41.29	-23.01	PASS
			2384.076	-41.63	-13.01	PASS
			2384.5	-42.09	-13.01	PASS
			2385.5	-41.77	-13.01	PASS
			2386.5	-41.88	-13.01	PASS
			2387.5	-41.77	-13.01	PASS
			2388.5	-41.20	-13.01	PASS
			2389.5	-41.32	-13.01	PASS
			2390.5	-41.00	-13.01	PASS
			2391.5	-37.22	-13.01	PASS
			2392.5	-36.36	-13.01	PASS
			2393.5	-35.00	-13.01	PASS
			2394.5	-30.61	-13.01	PASS
			2395.5	-30.79	-13.01	PASS
			2396.5	-29.56	-13.01	PASS
			2397.5	-29.12	-13.01	PASS
			2398.5	-28.93	-13.01	PASS
			2399.5	-27.65	-13.01	PASS
			2484	-42.45	-13.01	PASS
			2485	-43.08	-13.01	PASS
			2486	-42.80	-13.01	PASS
			2487	-43.01	-13.01	PASS
			2488	-43.21	-13.01	PASS
			2489	-43.27	-13.01	PASS
			2490	-43.24	-13.01	PASS
			2491	-43.27	-13.01	PASS
			2492	-42.99	-13.01	PASS
			2493	-42.55	-13.01	PASS
			2494	-42.73	-13.01	PASS
			2495	-43.12	-13.01	PASS
			2496	-43.67	-13.01	PASS
			2497	-42.45	-13.01	PASS
			2498	-43.16	-13.01	PASS
			2499	-42.48	-13.01	PASS
			2499.424	-43.23	-13.01	PASS
			2500.424	-43.48	-23.01	PASS
			2501.424	-43.81	-23.01	PASS
			2502.424	-43.23	-23.01	PASS
			2503.424	-43.51	-23.01	PASS
			2504.424	-42.24	-23.01	PASS
			2505.424	-43.91	-23.01	PASS
			2506.424	-43.15	-23.01	PASS
			2507.424	-43.69	-23.01	PASS

			2508.424	-43.47	-23.01	PASS
			2509.424	-42.91	-23.01	PASS
			2510.424	-42.98	-23.01	PASS
			2511.424	-42.40	-23.01	PASS
			2512.424	-44.10	-23.01	PASS
			2513.424	-43.64	-23.01	PASS
			2514.424	-43.36	-23.01	PASS
			2515.424	-42.94	-23.01	PASS
	Ant2	2412	2515.848	-42.38	-23.01	PASS
			2367.652	-43.18	-23.01	PASS
			2368.076	-43.16	-23.01	PASS
			2369.076	-43.79	-23.01	PASS
			2370.076	-43.22	-23.01	PASS
			2371.076	-43.37	-23.01	PASS
			2372.076	-43.08	-23.01	PASS
			2373.076	-43.32	-23.01	PASS
			2374.076	-42.76	-23.01	PASS
			2375.076	-43.02	-23.01	PASS
			2376.076	-42.54	-23.01	PASS
			2377.076	-41.82	-23.01	PASS
			2378.076	-42.44	-23.01	PASS
			2379.076	-42.20	-23.01	PASS
			2380.076	-43.10	-23.01	PASS
			2381.076	-43.05	-23.01	PASS
			2382.076	-43.06	-23.01	PASS
			2383.076	-42.87	-23.01	PASS
			2384.076	-43.22	-13.01	PASS
			2384.5	-42.23	-13.01	PASS
			2385.5	-42.56	-13.01	PASS
			2386.5	-42.37	-13.01	PASS
			2387.5	-42.37	-13.01	PASS
			2388.5	-41.90	-13.01	PASS
			2389.5	-42.54	-13.01	PASS
			2390.5	-42.36	-13.01	PASS
			2391.5	-40.22	-13.01	PASS
			2392.5	-41.38	-13.01	PASS
			2393.5	-41.26	-13.01	PASS
			2394.5	-41.27	-13.01	PASS
			2395.5	-40.76	-13.01	PASS
			2396.5	-38.69	-13.01	PASS
			2397.5	-39.67	-13.01	PASS
			2398.5	-38.24	-13.01	PASS
			2399.5	-37.81	-13.01	PASS
			2484	-41.24	-13.01	PASS
			2485	-42.65	-13.01	PASS
			2486	-43.33	-13.01	PASS
			2487	-42.71	-13.01	PASS
			2488	-43.70	-13.01	PASS
			2489	-43.39	-13.01	PASS
			2490	-43.60	-13.01	PASS
			2491	-43.51	-13.01	PASS
			2492	-43.18	-13.01	PASS
			2493	-42.62	-13.01	PASS
			2494	-43.25	-13.01	PASS
			2495	-43.34	-13.01	PASS
			2496	-43.59	-13.01	PASS
			2497	-43.46	-13.01	PASS
			2498	-42.09	-13.01	PASS
			2499	-42.86	-13.01	PASS
			2499.424	-43.12	-13.01	PASS
			2500.424	-43.32	-23.01	PASS

			2501.424	-43.61	-23.01	PASS
			2502.424	-43.84	-23.01	PASS
			2503.424	-43.63	-23.01	PASS
			2504.424	-43.18	-23.01	PASS
			2505.424	-43.78	-23.01	PASS
			2506.424	-42.92	-23.01	PASS
			2507.424	-42.78	-23.01	PASS
			2508.424	-43.65	-23.01	PASS
			2509.424	-43.82	-23.01	PASS
			2510.424	-43.32	-23.01	PASS
			2511.424	-43.21	-23.01	PASS
			2512.424	-43.52	-23.01	PASS
			2513.424	-43.58	-23.01	PASS
			2514.424	-43.31	-23.01	PASS
			2515.424	-43.86	-23.01	PASS
			2515.848	-43.21	-23.01	PASS
	Ant1	2472	2367.572	-43.24	-23.01	PASS
			2368.036	-42.80	-23.01	PASS
			2369.036	-42.65	-23.01	PASS
			2370.036	-43.16	-23.01	PASS
			2371.036	-42.80	-23.01	PASS
			2372.036	-43.30	-23.01	PASS
			2373.036	-43.06	-23.01	PASS
			2374.036	-43.20	-23.01	PASS
			2375.036	-43.22	-23.01	PASS
			2376.036	-42.19	-23.01	PASS
			2377.036	-42.83	-23.01	PASS
			2378.036	-41.18	-23.01	PASS
			2379.036	-42.50	-23.01	PASS
			2380.036	-42.31	-23.01	PASS
			2381.036	-43.01	-23.01	PASS
			2382.036	-42.58	-23.01	PASS
			2383.036	-42.59	-23.01	PASS
			2384.036	-42.55	-13.01	PASS
			2384.5	-42.66	-13.01	PASS
			2385.5	-42.24	-13.01	PASS
			2386.5	-41.60	-13.01	PASS
			2387.5	-42.58	-13.01	PASS
			2388.5	-41.70	-13.01	PASS
			2389.5	-41.64	-13.01	PASS
			2390.5	-42.55	-13.01	PASS
			2391.5	-43.07	-13.01	PASS
			2392.5	-42.33	-13.01	PASS
			2393.5	-42.43	-13.01	PASS
			2394.5	-41.85	-13.01	PASS
			2395.5	-42.35	-13.01	PASS
			2396.5	-41.99	-13.01	PASS
			2397.5	-42.59	-13.01	PASS
			2398.5	-42.66	-13.01	PASS
			2399.5	-42.32	-13.01	PASS
			2484	-31.77	-13.01	PASS
			2485	-31.76	-13.01	PASS
			2486	-34.61	-13.01	PASS
			2487	-34.81	-13.01	PASS
			2488	-38.35	-13.01	PASS
			2489	-36.69	-13.01	PASS
			2490	-38.26	-13.01	PASS
			2491	-41.88	-13.01	PASS
			2492	-41.42	-13.01	PASS
			2493	-41.85	-13.01	PASS
			2494	-42.96	-13.01	PASS

			2495	-42.48	-13.01	PASS
			2496	-42.19	-13.01	PASS
			2497	-41.80	-13.01	PASS
			2498	-42.03	-13.01	PASS
			2499	-42.73	-13.01	PASS
			2499.464	-42.12	-13.01	PASS
			2500.464	-42.77	-23.01	PASS
			2501.464	-42.63	-23.01	PASS
			2502.464	-42.44	-23.01	PASS
			2503.464	-42.24	-23.01	PASS
			2504.464	-42.60	-23.01	PASS
			2505.464	-43.21	-23.01	PASS
			2506.464	-41.71	-23.01	PASS
			2507.464	-42.69	-23.01	PASS
			2508.464	-41.77	-23.01	PASS
			2509.464	-42.87	-23.01	PASS
			2510.464	-43.07	-23.01	PASS
			2511.464	-43.23	-23.01	PASS
			2512.464	-42.91	-23.01	PASS
			2513.464	-42.59	-23.01	PASS
			2514.464	-43.00	-23.01	PASS
			2515.464	-42.09	-23.01	PASS
			2515.928	-42.41	-23.01	PASS
	Ant2	2472	2367.652	-43.46	-23.01	PASS
			2368.076	-41.52	-23.01	PASS
			2369.076	-42.43	-23.01	PASS
			2370.076	-42.98	-23.01	PASS
			2371.076	-42.52	-23.01	PASS
			2372.076	-43.44	-23.01	PASS
			2373.076	-42.30	-23.01	PASS
			2374.076	-43.22	-23.01	PASS
			2375.076	-42.40	-23.01	PASS
			2376.076	-42.95	-23.01	PASS
			2377.076	-43.22	-23.01	PASS
			2378.076	-43.42	-23.01	PASS
			2379.076	-42.31	-23.01	PASS
			2380.076	-42.38	-23.01	PASS
			2381.076	-42.83	-23.01	PASS
			2382.076	-42.23	-23.01	PASS
			2383.076	-43.20	-23.01	PASS
			2384.076	-41.89	-13.01	PASS
			2384.5	-42.37	-13.01	PASS
			2385.5	-43.05	-13.01	PASS
			2386.5	-42.63	-13.01	PASS
			2387.5	-42.36	-13.01	PASS
			2388.5	-42.74	-13.01	PASS
			2389.5	-42.49	-13.01	PASS
			2390.5	-42.75	-13.01	PASS
			2391.5	-41.20	-13.01	PASS
			2392.5	-42.47	-13.01	PASS
			2393.5	-43.14	-13.01	PASS
			2394.5	-42.72	-13.01	PASS
			2395.5	-42.01	-13.01	PASS
			2396.5	-42.04	-13.01	PASS
			2397.5	-41.56	-13.01	PASS
			2398.5	-42.48	-13.01	PASS
			2399.5	-42.31	-13.01	PASS
			2484	-35.71	-13.01	PASS
			2485	-33.69	-13.01	PASS
			2486	-36.96	-13.01	PASS
			2487	-37.45	-13.01	PASS

			2488	-38.40	-13.01	PASS
			2489	-39.25	-13.01	PASS
			2490	-39.45	-13.01	PASS
			2491	-40.16	-13.01	PASS
			2492	-41.96	-13.01	PASS
			2493	-41.13	-13.01	PASS
			2494	-41.37	-13.01	PASS
			2495	-41.49	-13.01	PASS
			2496	-41.01	-13.01	PASS
			2497	-41.74	-13.01	PASS
			2498	-42.65	-13.01	PASS
			2499	-40.53	-13.01	PASS
			2499.424	-41.75	-13.01	PASS
			2500.424	-40.77	-23.01	PASS
			2501.424	-42.16	-23.01	PASS
			2502.424	-41.91	-23.01	PASS
			2503.424	-42.39	-23.01	PASS
			2504.424	-42.21	-23.01	PASS
			2505.424	-41.51	-23.01	PASS
			2506.424	-42.66	-23.01	PASS
			2507.424	-42.53	-23.01	PASS
			2508.424	-42.39	-23.01	PASS
			2509.424	-42.87	-23.01	PASS
			2510.424	-42.96	-23.01	PASS
			2511.424	-42.46	-23.01	PASS
			2512.424	-41.65	-23.01	PASS
			2513.424	-41.51	-23.01	PASS
			2514.424	-41.71	-23.01	PASS
			2515.424	-42.55	-23.01	PASS
11N20MIMO	Ant1	2412	2515.848	-42.88	-23.01	PASS
			2367.652	-42.70	-23.01	PASS
			2368.076	-43.12	-23.01	PASS
			2369.076	-43.25	-23.01	PASS
			2370.076	-42.88	-23.01	PASS
			2371.076	-43.11	-23.01	PASS
			2372.076	-43.32	-23.01	PASS
			2373.076	-43.51	-23.01	PASS
			2374.076	-43.22	-23.01	PASS
			2375.076	-41.85	-23.01	PASS
			2376.076	-43.08	-23.01	PASS
			2377.076	-43.24	-23.01	PASS
			2378.076	-42.97	-23.01	PASS
			2379.076	-43.13	-23.01	PASS
			2380.076	-42.43	-23.01	PASS
			2381.076	-42.41	-23.01	PASS
			2382.076	-42.50	-23.01	PASS
			2383.076	-43.03	-23.01	PASS
			2384.076	-42.72	-13.01	PASS
			2384.5	-43.11	-13.01	PASS
			2385.5	-41.77	-13.01	PASS
			2386.5	-42.22	-13.01	PASS
			2387.5	-42.48	-13.01	PASS
			2388.5	-42.55	-13.01	PASS
			2389.5	-42.84	-13.01	PASS
			2390.5	-42.49	-13.01	PASS
			2391.5	-38.25	-13.01	PASS
			2392.5	-38.00	-13.01	PASS
			2393.5	-35.14	-13.01	PASS
			2394.5	-34.14	-13.01	PASS
			2395.5	-37.49	-13.01	PASS
			2396.5	-31.95	-13.01	PASS



			2397.5	-33.34	-13.01	PASS
			2398.5	-31.26	-13.01	PASS
			2399.5	-30.79	-13.01	PASS
			2484	-43.92	-13.01	PASS
			2485	-42.78	-13.01	PASS
			2486	-43.74	-13.01	PASS
			2487	-42.84	-13.01	PASS
			2488	-43.21	-13.01	PASS
			2489	-42.55	-13.01	PASS
			2490	-43.43	-13.01	PASS
			2491	-42.78	-13.01	PASS
			2492	-43.58	-13.01	PASS
			2493	-43.68	-13.01	PASS
			2494	-43.62	-13.01	PASS
			2495	-43.36	-13.01	PASS
			2496	-44.20	-13.01	PASS
			2497	-44.25	-13.01	PASS
			2498	-43.65	-13.01	PASS
			2499	-43.58	-13.01	PASS
			2499.424	-43.21	-13.01	PASS
			2500.424	-43.62	-23.01	PASS
			2501.424	-43.82	-23.01	PASS
			2502.424	-43.63	-23.01	PASS
			2503.424	-43.33	-23.01	PASS
			2504.424	-43.86	-23.01	PASS
			2505.424	-42.24	-23.01	PASS
			2506.424	-43.14	-23.01	PASS
			2507.424	-43.45	-23.01	PASS
			2508.424	-42.99	-23.01	PASS
			2509.424	-42.38	-23.01	PASS
			2510.424	-43.84	-23.01	PASS
			2511.424	-43.42	-23.01	PASS
			2512.424	-42.91	-23.01	PASS
			2513.424	-43.72	-23.01	PASS
			2514.424	-44.01	-23.01	PASS
			2515.424	-44.66	-23.01	PASS
			2515.848	-43.67	-23.01	PASS
	Ant2	2412	2367.652	-42.89	-23.01	PASS
			2368.076	-43.66	-23.01	PASS
			2369.076	-43.67	-23.01	PASS
			2370.076	-43.65	-23.01	PASS
			2371.076	-43.40	-23.01	PASS
			2372.076	-42.55	-23.01	PASS
			2373.076	-43.23	-23.01	PASS
			2374.076	-43.65	-23.01	PASS
			2375.076	-42.73	-23.01	PASS
			2376.076	-43.05	-23.01	PASS
			2377.076	-42.51	-23.01	PASS
			2378.076	-42.88	-23.01	PASS
			2379.076	-43.50	-23.01	PASS
			2380.076	-42.86	-23.01	PASS
			2381.076	-43.42	-23.01	PASS
			2382.076	-43.30	-23.01	PASS
			2383.076	-43.42	-23.01	PASS
			2384.076	-43.56	-13.01	PASS
			2384.5	-43.58	-13.01	PASS
			2385.5	-42.90	-13.01	PASS
			2386.5	-42.75	-13.01	PASS
			2387.5	-43.46	-13.01	PASS
			2388.5	-42.19	-13.01	PASS
			2389.5	-43.08	-13.01	PASS

			2390.5	-43.13	-13.01	PASS
			2391.5	-43.37	-13.01	PASS
			2392.5	-42.68	-13.01	PASS
			2393.5	-42.93	-13.01	PASS
			2394.5	-41.93	-13.01	PASS
			2395.5	-41.91	-13.01	PASS
			2396.5	-42.12	-13.01	PASS
			2397.5	-41.67	-13.01	PASS
			2398.5	-41.69	-13.01	PASS
			2399.5	-39.08	-13.01	PASS
			2484	-44.20	-13.01	PASS
			2485	-43.62	-13.01	PASS
			2486	-44.21	-13.01	PASS
			2487	-44.33	-13.01	PASS
			2488	-44.24	-13.01	PASS
			2489	-43.72	-13.01	PASS
			2490	-42.74	-13.01	PASS
			2491	-43.97	-13.01	PASS
			2492	-43.55	-13.01	PASS
			2493	-44.10	-13.01	PASS
			2494	-44.18	-13.01	PASS
			2495	-42.16	-13.01	PASS
			2496	-43.96	-13.01	PASS
			2497	-42.77	-13.01	PASS
			2498	-42.76	-13.01	PASS
			2499	-43.32	-13.01	PASS
			2499.424	-43.55	-13.01	PASS
			2500.424	-42.30	-23.01	PASS
			2501.424	-43.09	-23.01	PASS
			2502.424	-44.02	-23.01	PASS
			2503.424	-43.77	-23.01	PASS
			2504.424	-43.95	-23.01	PASS
			2505.424	-42.27	-23.01	PASS
			2506.424	-44.00	-23.01	PASS
			2507.424	-42.63	-23.01	PASS
			2508.424	-43.58	-23.01	PASS
			2509.424	-43.93	-23.01	PASS
			2510.424	-44.05	-23.01	PASS
			2511.424	-43.25	-23.01	PASS
			2512.424	-43.89	-23.01	PASS
			2513.424	-43.13	-23.01	PASS
			2514.424	-43.75	-23.01	PASS
			2515.424	-43.80	-23.01	PASS
			2515.848	-43.83	-23.01	PASS
	Ant1	2472	2364.878	-43.45	-23.01	PASS
			2365.256	-42.97	-23.01	PASS
			2365.878	-42.06	-23.01	PASS
			2366.878	-42.78	-23.01	PASS
			2367.878	-43.68	-23.01	PASS
			2368.878	-43.37	-23.01	PASS
			2369.878	-43.29	-23.01	PASS
			2370.878	-43.17	-23.01	PASS
			2371.878	-42.26	-23.01	PASS
			2372.878	-43.08	-23.01	PASS
			2373.878	-43.26	-23.01	PASS
			2374.878	-42.98	-23.01	PASS
			2375.878	-42.95	-23.01	PASS
			2376.878	-43.46	-23.01	PASS
			2377.878	-42.61	-23.01	PASS
			2378.878	-42.66	-23.01	PASS
			2379.878	-42.67	-23.01	PASS

			2380.878	-42.65	-23.01	PASS
			2381.878	-42.98	-23.01	PASS
			2382.5	-43.16	-13.01	PASS
			2382.878	-43.13	-13.01	PASS
			2383.5	-42.47	-13.01	PASS
			2384.5	-43.06	-13.01	PASS
			2385.5	-41.55	-13.01	PASS
			2386.5	-42.90	-13.01	PASS
			2387.5	-42.73	-13.01	PASS
			2388.5	-42.28	-13.01	PASS
			2389.5	-43.11	-13.01	PASS
			2390.5	-42.62	-13.01	PASS
			2391.5	-42.24	-13.01	PASS
			2392.5	-42.93	-13.01	PASS
			2393.5	-42.19	-13.01	PASS
			2394.5	-42.37	-13.01	PASS
			2395.5	-42.83	-13.01	PASS
			2396.5	-42.16	-13.01	PASS
			2397.5	-42.75	-13.01	PASS
			2398.5	-43.00	-13.01	PASS
			2399.5	-43.13	-13.01	PASS
			2484	-30.76	-13.01	PASS
			2485	-31.92	-13.01	PASS
			2486	-35.85	-13.01	PASS
			2487	-36.82	-13.01	PASS
			2488	-35.76	-13.01	PASS
			2489	-37.79	-13.01	PASS
			2490	-40.49	-13.01	PASS
			2491	-40.87	-13.01	PASS
			2492	-41.48	-13.01	PASS
			2493	-41.40	-13.01	PASS
			2494	-41.76	-13.01	PASS
			2495	-42.39	-13.01	PASS
			2496	-42.44	-13.01	PASS
			2497	-43.30	-13.01	PASS
			2498	-43.08	-13.01	PASS
			2499	-42.68	-13.01	PASS
			2500	-42.46	-13.01	PASS
			2500.622	-42.52	-13.01	PASS
			2501	-43.27	-13.01	PASS
			2501.622	-43.18	-23.01	PASS
			2502.622	-43.19	-23.01	PASS
			2503.622	-42.11	-23.01	PASS
			2504.622	-42.80	-23.01	PASS
			2505.622	-42.50	-23.01	PASS
			2506.622	-43.32	-23.01	PASS
			2507.622	-42.79	-23.01	PASS
			2508.622	-43.07	-23.01	PASS
			2509.622	-42.83	-23.01	PASS
			2510.622	-42.32	-23.01	PASS
			2511.622	-42.98	-23.01	PASS
			2512.622	-43.32	-23.01	PASS
2513.622	-42.54	-23.01	PASS			
2514.622	-42.58	-23.01	PASS			
2515.622	-42.71	-23.01	PASS			
2516.622	-42.69	-23.01	PASS			
2517.622	-42.96	-23.01	PASS			
2518.244	-43.20	-23.01	PASS			
2518.622	-42.33	-23.01	PASS			
Ant2	2472	2364.878	-42.18	-23.01	PASS	
		2365.256	-43.17	-23.01	PASS	

			2365.878	-43.62	-23.01	PASS
			2366.878	-43.91	-23.01	PASS
			2367.878	-44.15	-23.01	PASS
			2368.878	-43.20	-23.01	PASS
			2369.878	-43.64	-23.01	PASS
			2370.878	-43.51	-23.01	PASS
			2371.878	-43.50	-23.01	PASS
			2372.878	-43.19	-23.01	PASS
			2373.878	-42.98	-23.01	PASS
			2374.878	-42.75	-23.01	PASS
			2375.878	-43.45	-23.01	PASS
			2376.878	-43.74	-23.01	PASS
			2377.878	-43.82	-23.01	PASS
			2378.878	-43.12	-23.01	PASS
			2379.878	-42.47	-23.01	PASS
			2380.878	-43.29	-23.01	PASS
			2381.878	-43.81	-23.01	PASS
			2382.5	-43.42	-13.01	PASS
			2382.878	-43.06	-13.01	PASS
			2383.5	-43.68	-13.01	PASS
			2384.5	-42.76	-13.01	PASS
			2385.5	-42.93	-13.01	PASS
			2386.5	-43.83	-13.01	PASS
			2387.5	-42.91	-13.01	PASS
			2388.5	-42.61	-13.01	PASS
			2389.5	-43.17	-13.01	PASS
			2390.5	-43.03	-13.01	PASS
			2391.5	-42.57	-13.01	PASS
			2392.5	-43.40	-13.01	PASS
			2393.5	-42.26	-13.01	PASS
			2394.5	-43.24	-13.01	PASS
			2395.5	-43.81	-13.01	PASS
			2396.5	-42.95	-13.01	PASS
			2397.5	-43.07	-13.01	PASS
			2398.5	-42.28	-13.01	PASS
			2399.5	-43.25	-13.01	PASS
			2484	-39.33	-13.01	PASS
			2485	-39.94	-13.01	PASS
			2486	-41.07	-13.01	PASS
			2487	-41.01	-13.01	PASS
			2488	-41.79	-13.01	PASS
			2489	-41.44	-13.01	PASS
			2490	-42.57	-13.01	PASS
			2491	-41.78	-13.01	PASS
			2492	-42.76	-13.01	PASS
			2493	-41.46	-13.01	PASS
			2494	-42.28	-13.01	PASS
			2495	-42.74	-13.01	PASS
			2496	-42.60	-13.01	PASS
			2497	-43.30	-13.01	PASS
			2498	-43.34	-13.01	PASS
			2499	-42.95	-13.01	PASS
			2500	-42.11	-13.01	PASS
			2500.622	-43.11	-13.01	PASS
			2501	-42.78	-13.01	PASS
			2501.622	-43.07	-23.01	PASS
			2502.622	-43.45	-23.01	PASS
			2503.622	-43.13	-23.01	PASS
			2504.622	-43.21	-23.01	PASS
			2505.622	-43.33	-23.01	PASS
			2506.622	-43.13	-23.01	PASS

			2507.622	-43.14	-23.01	PASS
			2508.622	-43.54	-23.01	PASS
			2509.622	-43.50	-23.01	PASS
			2510.622	-43.20	-23.01	PASS
			2511.622	-43.73	-23.01	PASS
			2512.622	-43.81	-23.01	PASS
			2513.622	-43.55	-23.01	PASS
			2514.622	-42.77	-23.01	PASS
			2515.622	-43.16	-23.01	PASS
			2516.622	-43.66	-23.01	PASS
			2517.622	-43.18	-23.01	PASS
			2518.244	-42.61	-23.01	PASS
11N40MIMO	Ant1	2422	2518.622	-43.49	-23.01	PASS
			2328.536	-43.73	-23.01	PASS
			2328.572	-43.01	-23.01	PASS
			2329.536	-43.86	-23.01	PASS
			2330.536	-43.60	-23.01	PASS
			2331.536	-42.56	-23.01	PASS
			2332.536	-43.00	-23.01	PASS
			2333.536	-41.61	-23.01	PASS
			2334.536	-43.32	-23.01	PASS
			2335.536	-42.06	-23.01	PASS
			2336.536	-44.01	-23.01	PASS
			2337.536	-42.80	-23.01	PASS
			2338.536	-43.60	-23.01	PASS
			2339.536	-43.15	-23.01	PASS
			2340.536	-43.50	-23.01	PASS
			2341.536	-42.22	-23.01	PASS
			2342.536	-43.00	-23.01	PASS
			2343.536	-43.91	-23.01	PASS
			2344.536	-43.84	-23.01	PASS
			2345.536	-42.84	-23.01	PASS
			2346.536	-42.80	-23.01	PASS
			2347.536	-43.80	-23.01	PASS
			2348.536	-43.22	-23.01	PASS
			2349.536	-43.11	-23.01	PASS
			2350.536	-43.63	-23.01	PASS
			2351.536	-43.59	-23.01	PASS
			2352.536	-42.23	-23.01	PASS
			2353.536	-43.93	-23.01	PASS
			2354.536	-43.87	-23.01	PASS
			2355.536	-42.47	-23.01	PASS
			2356.536	-42.90	-23.01	PASS
			2357.536	-43.64	-23.01	PASS
			2358.536	-43.36	-23.01	PASS
			2359.536	-43.35	-23.01	PASS
			2360.536	-43.51	-23.01	PASS
			2361.536	-41.88	-23.01	PASS
			2362.536	-42.14	-23.01	PASS
			2363.536	-42.57	-23.01	PASS
			2364.5	-43.22	-13.01	PASS
			2364.536	-43.35	-13.01	PASS
			2365.5	-42.92	-13.01	PASS
			2366.5	-42.77	-13.01	PASS
			2367.5	-42.49	-13.01	PASS
			2368.5	-42.56	-13.01	PASS
			2369.5	-43.27	-13.01	PASS
			2370.5	-42.06	-13.01	PASS
			2371.5	-42.67	-13.01	PASS
			2372.5	-42.75	-13.01	PASS
			2373.5	-42.18	-13.01	PASS

			2374.5	-42.13	-13.01	PASS
			2375.5	-41.29	-13.01	PASS
			2376.5	-40.03	-13.01	PASS
			2377.5	-39.74	-13.01	PASS
			2378.5	-39.57	-13.01	PASS
			2379.5	-38.00	-13.01	PASS
			2380.5	-39.10	-13.01	PASS
			2381.5	-38.40	-13.01	PASS
			2382.5	-34.77	-13.01	PASS
			2383.5	-36.07	-13.01	PASS
			2384.5	-35.84	-13.01	PASS
			2385.5	-35.38	-13.01	PASS
			2386.5	-34.35	-13.01	PASS
			2387.5	-33.44	-13.01	PASS
			2388.5	-33.93	-13.01	PASS
			2389.5	-32.81	-13.01	PASS
			2390.5	-31.97	-13.01	PASS
			2391.5	-31.11	-13.01	PASS
			2392.5	-31.25	-13.01	PASS
			2393.5	-31.77	-13.01	PASS
			2394.5	-28.44	-13.01	PASS
			2395.5	-29.60	-13.01	PASS
			2396.5	-29.86	-13.01	PASS
			2397.5	-27.83	-13.01	PASS
			2398.5	-27.28	-13.01	PASS
			2399.5	-27.67	-13.01	PASS
			2484	-43.69	-13.01	PASS
			2485	-43.04	-13.01	PASS
			2486	-42.35	-13.01	PASS
			2487	-43.25	-13.01	PASS
			2488	-43.05	-13.01	PASS
			2489	-43.18	-13.01	PASS
			2490	-43.66	-13.01	PASS
			2491	-42.57	-13.01	PASS
			2492	-43.61	-13.01	PASS
			2493	-43.70	-13.01	PASS
			2494	-43.81	-13.01	PASS
			2495	-43.47	-13.01	PASS
			2496	-42.94	-13.01	PASS
			2497	-43.34	-13.01	PASS
			2498	-42.47	-13.01	PASS
			2499	-42.93	-13.01	PASS
			2500	-43.37	-13.01	PASS
			2501	-43.35	-13.01	PASS
			2502	-43.84	-13.01	PASS
			2503	-43.14	-13.01	PASS
			2504	-43.72	-13.01	PASS
			2505	-43.34	-13.01	PASS
			2506	-43.47	-13.01	PASS
			2507	-43.20	-13.01	PASS
			2508	-43.21	-13.01	PASS
			2509	-42.95	-13.01	PASS
			2510	-42.75	-13.01	PASS
			2511	-43.59	-13.01	PASS
			2512	-43.39	-13.01	PASS
			2513	-43.72	-13.01	PASS
			2514	-43.59	-13.01	PASS
			2515	-43.70	-13.01	PASS
			2516	-43.85	-13.01	PASS
			2517	-42.77	-13.01	PASS
			2518	-43.14	-13.01	PASS

			2518.964	-43.01	-13.01	PASS
			2519.964	-42.57	-13.01	PASS
			2520.964	-43.15	-23.01	PASS
			2521.964	-42.97	-23.01	PASS
			2522.964	-43.03	-23.01	PASS
			2523.964	-43.97	-23.01	PASS
			2524.964	-43.44	-23.01	PASS
			2525.964	-43.89	-23.01	PASS
			2526.964	-43.26	-23.01	PASS
			2527.964	-43.95	-23.01	PASS
			2528.964	-43.36	-23.01	PASS
			2529.964	-43.26	-23.01	PASS
			2530.964	-43.37	-23.01	PASS
			2531.964	-43.26	-23.01	PASS
			2532.964	-43.92	-23.01	PASS
			2533.964	-43.55	-23.01	PASS
			2534.964	-43.15	-23.01	PASS
			2535.964	-43.73	-23.01	PASS
			2536.964	-44.24	-23.01	PASS
			2537.964	-43.66	-23.01	PASS
			2538.964	-43.64	-23.01	PASS
			2539.964	-43.97	-23.01	PASS
			2540.964	-43.31	-23.01	PASS
			2541.964	-43.69	-23.01	PASS
			2542.964	-44.29	-23.01	PASS
			2543.964	-44.02	-23.01	PASS
			2544.964	-43.29	-23.01	PASS
			2545.964	-43.82	-23.01	PASS
			2546.964	-42.87	-23.01	PASS
			2547.964	-43.64	-23.01	PASS
			2548.964	-43.96	-23.01	PASS
			2549.964	-43.05	-23.01	PASS
			2550.964	-42.69	-23.01	PASS
			2551.964	-43.90	-23.01	PASS
			2552.964	-43.35	-23.01	PASS
			2553.964	-43.95	-23.01	PASS
			2554.928	-43.67	-23.01	PASS
			2554.964	-43.66	-23.01	PASS
			2554.964	-44.17	-23.01	PASS
			2328.412	-43.87	-23.01	PASS
			2328.456	-44.00	-23.01	PASS
			2329.456	-44.25	-23.01	PASS
			2330.456	-43.04	-23.01	PASS
			2331.456	-43.94	-23.01	PASS
			2332.456	-43.79	-23.01	PASS
			2333.456	-43.79	-23.01	PASS
			2334.456	-43.38	-23.01	PASS
			2335.456	-43.53	-23.01	PASS
			2336.456	-43.76	-23.01	PASS
			2337.456	-43.58	-23.01	PASS
			2338.456	-44.11	-23.01	PASS
			2339.456	-44.28	-23.01	PASS
			2340.456	-43.76	-23.01	PASS
			2341.456	-44.22	-23.01	PASS
			2342.456	-44.44	-23.01	PASS
			2343.456	-43.20	-23.01	PASS
			2344.456	-44.39	-23.01	PASS
			2345.456	-44.03	-23.01	PASS
			2346.456	-44.24	-23.01	PASS
			2347.456	-44.18	-23.01	PASS
			2348.456	-44.13	-23.01	PASS

			2349.456	-43.69	-23.01	PASS
			2350.456	-44.02	-23.01	PASS
			2351.456	-43.21	-23.01	PASS
			2352.456	-43.49	-23.01	PASS
			2353.456	-43.72	-23.01	PASS
			2354.456	-43.63	-23.01	PASS
			2355.456	-43.87	-23.01	PASS
			2356.456	-43.05	-23.01	PASS
			2357.456	-42.89	-23.01	PASS
			2358.456	-43.35	-23.01	PASS
			2359.456	-43.01	-23.01	PASS
			2360.456	-43.65	-23.01	PASS
			2361.456	-42.05	-23.01	PASS
			2362.456	-43.67	-23.01	PASS
			2363.456	-43.68	-23.01	PASS
			2364.456	-43.33	-13.01	PASS
			2364.5	-43.31	-13.01	PASS
			2365.5	-43.40	-13.01	PASS
			2366.5	-42.71	-13.01	PASS
			2367.5	-43.70	-13.01	PASS
			2368.5	-43.08	-13.01	PASS
			2369.5	-43.11	-13.01	PASS
			2370.5	-42.99	-13.01	PASS
			2371.5	-42.22	-13.01	PASS
			2372.5	-43.11	-13.01	PASS
			2373.5	-43.01	-13.01	PASS
			2374.5	-43.82	-13.01	PASS
			2375.5	-43.15	-13.01	PASS
			2376.5	-42.93	-13.01	PASS
			2377.5	-42.11	-13.01	PASS
			2378.5	-42.00	-13.01	PASS
			2379.5	-43.55	-13.01	PASS
			2380.5	-43.31	-13.01	PASS
			2381.5	-42.11	-13.01	PASS
			2382.5	-42.89	-13.01	PASS
			2383.5	-42.60	-13.01	PASS
			2384.5	-43.20	-13.01	PASS
			2385.5	-42.01	-13.01	PASS
			2386.5	-41.39	-13.01	PASS
			2387.5	-42.64	-13.01	PASS
			2388.5	-42.21	-13.01	PASS
			2389.5	-41.68	-13.01	PASS
			2390.5	-41.57	-13.01	PASS
			2391.5	-41.06	-13.01	PASS
			2392.5	-39.59	-13.01	PASS
			2393.5	-42.03	-13.01	PASS
			2394.5	-40.65	-13.01	PASS
			2395.5	-39.02	-13.01	PASS
			2396.5	-40.86	-13.01	PASS
			2397.5	-39.09	-13.01	PASS
			2398.5	-39.66	-13.01	PASS
			2399.5	-37.27	-13.01	PASS
			2484	-43.81	-13.01	PASS
			2485	-43.41	-13.01	PASS
			2486	-43.67	-13.01	PASS
			2487	-44.04	-13.01	PASS
			2488	-43.56	-13.01	PASS
			2489	-44.11	-13.01	PASS
			2490	-43.47	-13.01	PASS
			2491	-44.07	-13.01	PASS
			2492	-43.05	-13.01	PASS



			2493	-43.32	-13.01	PASS
			2494	-43.31	-13.01	PASS
			2495	-43.97	-13.01	PASS
			2496	-43.70	-13.01	PASS
			2497	-43.11	-13.01	PASS
			2498	-43.60	-13.01	PASS
			2499	-43.57	-13.01	PASS
			2500	-43.46	-13.01	PASS
			2501	-43.46	-13.01	PASS
			2502	-42.88	-13.01	PASS
			2503	-43.46	-13.01	PASS
			2504	-43.89	-13.01	PASS
			2505	-44.05	-13.01	PASS
			2506	-43.46	-13.01	PASS
			2507	-42.80	-13.01	PASS
			2508	-43.88	-13.01	PASS
			2509	-43.41	-13.01	PASS
			2510	-43.94	-13.01	PASS
			2511	-44.32	-13.01	PASS
			2512	-43.56	-13.01	PASS
			2513	-44.03	-13.01	PASS
			2514	-43.01	-13.01	PASS
			2515	-42.36	-13.01	PASS
			2516	-43.57	-13.01	PASS
			2517	-43.48	-13.01	PASS
			2518	-43.36	-13.01	PASS
			2519	-43.71	-13.01	PASS
			2519.044	-44.22	-13.01	PASS
			2520.044	-43.38	-23.01	PASS
			2521.044	-43.70	-23.01	PASS
			2522.044	-43.68	-23.01	PASS
			2523.044	-43.98	-23.01	PASS
			2524.044	-42.90	-23.01	PASS
			2525.044	-43.35	-23.01	PASS
			2526.044	-43.98	-23.01	PASS
			2527.044	-43.35	-23.01	PASS
			2528.044	-43.84	-23.01	PASS
			2529.044	-43.44	-23.01	PASS
			2530.044	-44.29	-23.01	PASS
			2531.044	-43.70	-23.01	PASS
			2532.044	-43.28	-23.01	PASS
			2533.044	-43.93	-23.01	PASS
			2534.044	-42.23	-23.01	PASS
			2535.044	-43.82	-23.01	PASS
			2536.044	-43.06	-23.01	PASS
			2537.044	-43.88	-23.01	PASS
			2538.044	-42.63	-23.01	PASS
			2539.044	-43.83	-23.01	PASS
			2540.044	-43.63	-23.01	PASS
			2541.044	-44.09	-23.01	PASS
			2542.044	-43.64	-23.01	PASS
			2543.044	-43.40	-23.01	PASS
			2544.044	-43.92	-23.01	PASS
			2545.044	-43.02	-23.01	PASS
			2546.044	-44.02	-23.01	PASS
			2547.044	-43.39	-23.01	PASS
			2548.044	-43.79	-23.01	PASS
			2549.044	-43.84	-23.01	PASS
			2550.044	-43.01	-23.01	PASS
			2551.044	-43.17	-23.01	PASS
			2552.044	-41.86	-23.01	PASS

			2553.044	-44.00	-23.01	PASS
			2554.044	-42.42	-23.01	PASS
			2555.044	-43.90	-23.01	PASS
			2555.088	-44.00	-23.01	PASS
Ant1	2462		2328.536	-43.91	-23.01	PASS
			2328.572	-44.34	-23.01	PASS
			2329.536	-42.41	-23.01	PASS
			2330.536	-44.12	-23.01	PASS
			2331.536	-43.69	-23.01	PASS
			2332.536	-43.96	-23.01	PASS
			2333.536	-43.58	-23.01	PASS
			2334.536	-43.99	-23.01	PASS
			2335.536	-42.59	-23.01	PASS
			2336.536	-44.06	-23.01	PASS
			2337.536	-43.83	-23.01	PASS
			2338.536	-44.18	-23.01	PASS
			2339.536	-43.64	-23.01	PASS
			2340.536	-42.84	-23.01	PASS
			2341.536	-43.95	-23.01	PASS
			2342.536	-42.38	-23.01	PASS
			2343.536	-42.19	-23.01	PASS
			2344.536	-44.16	-23.01	PASS
			2345.536	-43.36	-23.01	PASS
			2346.536	-43.48	-23.01	PASS
			2347.536	-43.86	-23.01	PASS
			2348.536	-43.76	-23.01	PASS
			2349.536	-43.17	-23.01	PASS
			2350.536	-43.36	-23.01	PASS
			2351.536	-43.77	-23.01	PASS
			2352.536	-43.17	-23.01	PASS
			2353.536	-43.70	-23.01	PASS
			2354.536	-43.15	-23.01	PASS
			2355.536	-43.48	-23.01	PASS
			2356.536	-43.50	-23.01	PASS
			2357.536	-43.69	-23.01	PASS
			2358.536	-43.21	-23.01	PASS
			2359.536	-43.01	-23.01	PASS
			2360.536	-43.93	-23.01	PASS
			2361.536	-42.92	-23.01	PASS
			2362.536	-43.75	-23.01	PASS
			2363.536	-42.63	-23.01	PASS
			2364.5	-44.37	-13.01	PASS
			2364.536	-43.79	-13.01	PASS
			2365.5	-43.08	-13.01	PASS
			2366.5	-44.19	-13.01	PASS
			2367.5	-43.65	-13.01	PASS
			2368.5	-43.31	-13.01	PASS
			2369.5	-43.47	-13.01	PASS
			2370.5	-43.81	-13.01	PASS
			2371.5	-42.44	-13.01	PASS
			2372.5	-43.21	-13.01	PASS
			2373.5	-42.41	-13.01	PASS
			2374.5	-43.68	-13.01	PASS
			2375.5	-43.37	-13.01	PASS
			2376.5	-43.06	-13.01	PASS
			2377.5	-44.25	-13.01	PASS
			2378.5	-44.10	-13.01	PASS
			2379.5	-42.72	-13.01	PASS
			2380.5	-43.22	-13.01	PASS
			2381.5	-42.97	-13.01	PASS
			2382.5	-42.16	-13.01	PASS

		2383.5	-41.93	-13.01	PASS
		2384.5	-43.62	-13.01	PASS
		2385.5	-43.24	-13.01	PASS
		2386.5	-43.87	-13.01	PASS
		2387.5	-43.79	-13.01	PASS
		2388.5	-43.39	-13.01	PASS
		2389.5	-43.15	-13.01	PASS
		2390.5	-43.11	-13.01	PASS
		2391.5	-43.22	-13.01	PASS
		2392.5	-43.70	-13.01	PASS
		2393.5	-43.70	-13.01	PASS
		2394.5	-41.71	-13.01	PASS
		2395.5	-43.30	-13.01	PASS
		2396.5	-43.09	-13.01	PASS
		2397.5	-42.88	-13.01	PASS
		2398.5	-43.29	-13.01	PASS
		2399.5	-41.66	-13.01	PASS
		2484	-34.76	-13.01	PASS
		2485	-34.86	-13.01	PASS
		2486	-34.96	-13.01	PASS
		2487	-35.42	-13.01	PASS
		2488	-35.09	-13.01	PASS
		2489	-37.07	-13.01	PASS
		2490	-38.30	-13.01	PASS
		2491	-38.19	-13.01	PASS
		2492	-37.85	-13.01	PASS
		2493	-39.22	-13.01	PASS
		2494	-39.42	-13.01	PASS
		2495	-39.76	-13.01	PASS
		2496	-40.14	-13.01	PASS
		2497	-39.64	-13.01	PASS
		2498	-40.92	-13.01	PASS
		2499	-40.01	-13.01	PASS
		2500	-41.22	-13.01	PASS
		2501	-40.91	-13.01	PASS
		2502	-42.07	-13.01	PASS
		2503	-42.59	-13.01	PASS
		2504	-42.49	-13.01	PASS
		2505	-42.98	-13.01	PASS
		2506	-43.47	-13.01	PASS
		2507	-43.60	-13.01	PASS
		2508	-43.07	-13.01	PASS
		2509	-43.53	-13.01	PASS
		2510	-43.60	-13.01	PASS
		2511	-43.49	-13.01	PASS
		2512	-43.19	-13.01	PASS
		2513	-42.10	-13.01	PASS
		2514	-42.68	-13.01	PASS
		2515	-43.09	-13.01	PASS
		2516	-41.92	-13.01	PASS
		2517	-43.64	-13.01	PASS
		2518	-43.30	-13.01	PASS
		2518.964	-42.74	-13.01	PASS
		2519	-43.01	-13.01	PASS
		2519.964	-44.33	-23.01	PASS
		2520.964	-43.79	-23.01	PASS
		2521.964	-43.66	-23.01	PASS
		2522.964	-43.86	-23.01	PASS
		2523.964	-43.91	-23.01	PASS
		2524.964	-43.76	-23.01	PASS
		2525.964	-43.78	-23.01	PASS


			2526.964	-43.60	-23.01	PASS
			2527.964	-42.89	-23.01	PASS
			2528.964	-43.03	-23.01	PASS
			2529.964	-42.64	-23.01	PASS
			2530.964	-44.18	-23.01	PASS
			2531.964	-41.48	-23.01	PASS
			2532.964	-43.75	-23.01	PASS
			2533.964	-43.48	-23.01	PASS
			2534.964	-43.50	-23.01	PASS
			2535.964	-42.48	-23.01	PASS
			2536.964	-43.29	-23.01	PASS
			2537.964	-43.28	-23.01	PASS
			2538.964	-43.29	-23.01	PASS
			2539.964	-43.89	-23.01	PASS
			2540.964	-43.54	-23.01	PASS
			2541.964	-43.17	-23.01	PASS
			2542.964	-44.07	-23.01	PASS
			2543.964	-43.46	-23.01	PASS
			2544.964	-44.13	-23.01	PASS
			2545.964	-44.01	-23.01	PASS
			2546.964	-43.66	-23.01	PASS
			2547.964	-43.57	-23.01	PASS
			2548.964	-43.11	-23.01	PASS
			2549.964	-42.29	-23.01	PASS
			2550.964	-43.93	-23.01	PASS
			2551.964	-43.22	-23.01	PASS
			2552.964	-43.54	-23.01	PASS
			2553.964	-43.75	-23.01	PASS
			2554.928	-43.51	-23.01	PASS
			2554.964	-43.33	-23.01	PASS
	Ant2	2462	2328.616	-43.24	-23.01	PASS
			2328.732	-43.65	-23.01	PASS
			2329.616	-43.94	-23.01	PASS
			2330.616	-42.09	-23.01	PASS
			2331.616	-44.68	-23.01	PASS
			2332.616	-43.92	-23.01	PASS
			2333.616	-43.14	-23.01	PASS
			2334.616	-42.85	-23.01	PASS
			2335.616	-43.38	-23.01	PASS
			2336.616	-43.74	-23.01	PASS
			2337.616	-43.77	-23.01	PASS
			2338.616	-43.22	-23.01	PASS
			2339.616	-43.30	-23.01	PASS
			2340.616	-43.77	-23.01	PASS
			2341.616	-43.59	-23.01	PASS
			2342.616	-42.92	-23.01	PASS
			2343.616	-43.60	-23.01	PASS
			2344.616	-42.96	-23.01	PASS
			2345.616	-43.22	-23.01	PASS
			2346.616	-43.50	-23.01	PASS
			2347.616	-42.60	-23.01	PASS
			2348.616	-43.89	-23.01	PASS
			2349.616	-43.66	-23.01	PASS
			2350.616	-43.25	-23.01	PASS
			2351.616	-43.75	-23.01	PASS
			2352.616	-43.28	-23.01	PASS
			2353.616	-43.19	-23.01	PASS
			2354.616	-43.75	-23.01	PASS
			2355.616	-43.53	-23.01	PASS
			2356.616	-43.25	-23.01	PASS
			2357.616	-42.51	-23.01	PASS

			2358.616	-43.68	-23.01	PASS
			2359.616	-43.45	-23.01	PASS
			2360.616	-43.98	-23.01	PASS
			2361.616	-43.39	-23.01	PASS
			2362.616	-41.97	-23.01	PASS
			2363.616	-42.89	-23.01	PASS
			2364.5	-43.45	-13.01	PASS
			2364.616	-43.66	-13.01	PASS
			2365.5	-43.53	-13.01	PASS
			2366.5	-43.41	-13.01	PASS
			2367.5	-43.40	-13.01	PASS
			2368.5	-42.71	-13.01	PASS
			2369.5	-42.96	-13.01	PASS
			2370.5	-43.52	-13.01	PASS
			2371.5	-42.73	-13.01	PASS
			2372.5	-43.20	-13.01	PASS
			2373.5	-42.56	-13.01	PASS
			2374.5	-42.03	-13.01	PASS
			2375.5	-43.53	-13.01	PASS
			2376.5	-43.14	-13.01	PASS
			2377.5	-43.25	-13.01	PASS
			2378.5	-42.80	-13.01	PASS
			2379.5	-43.38	-13.01	PASS
			2380.5	-43.22	-13.01	PASS
			2381.5	-43.40	-13.01	PASS
			2382.5	-43.52	-13.01	PASS
			2383.5	-43.28	-13.01	PASS
			2384.5	-43.32	-13.01	PASS
			2385.5	-43.52	-13.01	PASS
			2386.5	-43.18	-13.01	PASS
			2387.5	-42.64	-13.01	PASS
			2388.5	-43.56	-13.01	PASS
			2389.5	-43.34	-13.01	PASS
			2390.5	-43.19	-13.01	PASS
			2391.5	-42.68	-13.01	PASS
			2392.5	-41.94	-13.01	PASS
			2393.5	-43.00	-13.01	PASS
			2394.5	-43.48	-13.01	PASS
			2395.5	-43.25	-13.01	PASS
			2396.5	-43.33	-13.01	PASS
			2397.5	-42.90	-13.01	PASS
			2398.5	-42.97	-13.01	PASS
			2399.5	-41.78	-13.01	PASS
			2484	-34.60	-13.01	PASS
			2485	-35.10	-13.01	PASS
			2486	-35.17	-13.01	PASS
			2487	-36.12	-13.01	PASS
			2488	-35.76	-13.01	PASS
			2489	-36.96	-13.01	PASS
			2490	-37.50	-13.01	PASS
			2491	-38.35	-13.01	PASS
			2492	-38.45	-13.01	PASS
			2493	-38.90	-13.01	PASS
			2494	-39.24	-13.01	PASS
			2495	-39.88	-13.01	PASS
			2496	-40.11	-13.01	PASS
			2497	-40.60	-13.01	PASS
			2498	-41.16	-13.01	PASS
			2499	-41.33	-13.01	PASS
			2500	-41.15	-13.01	PASS
			2501	-41.84	-13.01	PASS


		2502	-43.07	-13.01	PASS
		2503	-42.47	-13.01	PASS
		2504	-42.71	-13.01	PASS
		2505	-41.99	-13.01	PASS
		2506	-42.11	-13.01	PASS
		2507	-43.34	-13.01	PASS
		2508	-43.04	-13.01	PASS
		2509	-43.58	-13.01	PASS
		2510	-42.60	-13.01	PASS
		2511	-43.47	-13.01	PASS
		2512	-43.16	-13.01	PASS
		2513	-43.26	-13.01	PASS
		2514	-42.37	-13.01	PASS
		2515	-42.61	-13.01	PASS
		2516	-42.07	-13.01	PASS
		2517	-42.85	-13.01	PASS
		2518	-41.29	-13.01	PASS
		2518.884	-43.70	-13.01	PASS
		2519	-43.12	-13.01	PASS
		2519.884	-43.76	-23.01	PASS
		2520.884	-43.87	-23.01	PASS
		2521.884	-43.04	-23.01	PASS
		2522.884	-43.49	-23.01	PASS
		2523.884	-43.14	-23.01	PASS
		2524.884	-42.92	-23.01	PASS
		2525.884	-43.79	-23.01	PASS
		2526.884	-42.31	-23.01	PASS
		2527.884	-43.14	-23.01	PASS
		2528.884	-42.84	-23.01	PASS
		2529.884	-43.08	-23.01	PASS
		2530.884	-43.45	-23.01	PASS
		2531.884	-43.70	-23.01	PASS
		2532.884	-43.38	-23.01	PASS
		2533.884	-43.55	-23.01	PASS
		2534.884	-42.94	-23.01	PASS
		2535.884	-44.13	-23.01	PASS
		2536.884	-43.95	-23.01	PASS
		2537.884	-43.45	-23.01	PASS
		2538.884	-43.87	-23.01	PASS
		2539.884	-43.94	-23.01	PASS
		2540.884	-43.71	-23.01	PASS
		2541.884	-43.00	-23.01	PASS
		2542.884	-43.34	-23.01	PASS
		2543.884	-43.49	-23.01	PASS
		2544.884	-42.56	-23.01	PASS
		2545.884	-42.04	-23.01	PASS
		2546.884	-44.16	-23.01	PASS
		2547.884	-43.77	-23.01	PASS
		2548.884	-42.96	-23.01	PASS
		2549.884	-43.43	-23.01	PASS
		2550.884	-43.67	-23.01	PASS
		2551.884	-43.33	-23.01	PASS
		2552.884	-42.53	-23.01	PASS
		2553.884	-43.78	-23.01	PASS
		2554.768	-43.82	-23.01	PASS
		2554.884	-42.82	-23.01	PASS

Note: Antenna gain has added into final result.


## Test Graphs




11BMIMO\_Ant2\_2412\_2483.5MHz to 2483.5MHz+2BW




11BMIMO\_Ant1\_2472\_2400MHz-2BW to 2400MHz





11BMIMO\_Ant1\_2472\_2483.5MHz to 2483.5MHz+2BW














## 11GMIMO Ant2 2472 2400MHz-2BW to 2400MHz




## 11GMIMO Ant2 2472 2483.5MHz to 2483.5MHz+2BW




## 11N20MIMO Ant1 2412 2400MHz-2BW to 2400MHz




11N20MIMO Ant1 2412 2483.5MHz to 2483.5MHz+2BW




11N20MIMO Ant2 2412 2400MHz-2BW to 2400MHz




11N20MIMO Ant2 2412 2483.5MHz to 2483.5MHz+2BW




11N20MIMO Ant1 2472 2400MHz-2BW to 2400MHz




11N20MIMO Ant1 2472 2483.5MHz to 2483.5MHz+2BW




11N20MIMO Ant2 2472 2400MHz-2BW to 2400MHz




11N20MIMO\_Ant2\_2472\_2483.5MHz to 2483.5MHz+2BW




11N40MIMO\_Ant1\_2422\_2400MHz-2BW to 2400MHz




11N40MIMO\_Ant1\_2422\_2483.5MHz to 2483.5MHz+2BW




11N40MIMO Ant2 2422 2400MHz-2BW to 2400MHz



11N40MIMO Ant2 2422 2483.5MHz to 2483.5MHz+2BW




11N40MIMO Ant1 2462 2400MHz-2BW to 2400MHz







11N40MIMO Ant1 2462 2483.5MHz to 2483.5MHz+2BW



11N40MIMO Ant2 2462 2400MHz-2BW to 2400MHz



11N40MIMO Ant2 2462 2483.5MHz to 2483.5MHz+2BW




**Appendix E: Receiver Blocking  
Test Result**

Test Mode	Antenna	Channel	Pmin [dBm]	Wanted signal [dBm]	Freq. [MHz]	CW [dBm]	PER [%]	Limit [%]	Verdict
11B	Ant1	2412	---	-64	2300	-32.25	6.90	<=10	PASS
			---	-64	2380	-32.25	6.90	<= 10	PASS
		2472	---	-64	2504	-32.25	1.60	<=10	PASS
			---	-64	2584	-32.25	1.60	<= 10	PASS

Note: The Maximum EIRP is 9.93dBm<10dBm and the EUT is an adaptive device, so it belongs to the receiver category 2.

Test Graphs



\*\*\*\*\* END OF REPORT \*\*\*\*\*